



L'articolo non è più disponibile.

Features :

Logistica

EUROLITE LED PAR-64 RGBA 10mm Short sil

PRO spotlight as LED DMX model

- 4 or 6 DMX channels selectable for numerous applications
- Equipped with 177 x 10 mm LEDs: 30 x red, 48 x green, 54 x blue and 45 x amber
- Sound-control via built-in microphone
- Beam angle approximately 36°
- Locking possibility at the mounting bracket
- Addressing and setting via control panel with LED display
- Preset (internal programs)
- RGBA color change
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Dimmer and Strobe settings via DMX
- Ready for connection with power cord and plug
- Also available as floor spot version
- Available in silver or black
- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX512 control via regular DMX controller
- Può funzionare in modalità 6; 4 CH DMX
- Controllabile via stand-alone; DMX

EUROLITE DMX LED Operator 2 controller

Compact DMX controller for easy application

- 8 control channels only suitable for special LED-spots (RGBA and RGBW)
- Select color mode for choosing single colors
- Internal programs
- Auto mode for running all programs
- Sound-control via built-in microphone
- Pause function
- Blackout function
- Control LEDs display current operating mode
- Program Select-fader for selecting the internal programs
- Speed-fader for adjusting the program-speed
- Strobe-effect with adjustable speed
- Additional fogger button for direct control of a DMX smoke machine (CH-7/8)
- Designed for standing operation, optional installation is customer's choice
- Suitable for 254 mm racks (10") with 4 units
- Power supply via enclosed 12 V DC power unit
- Può inviare fino a 8 canali DMX
- Controllabile via DMX; controllo della musica via microfono
- Custodia per mixer

OMNITRONIC Cavo XLR 3 poli 5m nero

Cavo audio con connettori XLR a 3 poli

Dati tecnici :

Peso:	11,29 kg
-------	----------

EUROLITE LED PAR-64 RGBA 10mm Short sil

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	27 W
Tipo di lampada:	Lampada a LED
Canali DMX:	6; 4
Attivazione:	Stand-alone; DMX
Fixtures disponibili per:	Light´J; LED PC-Control 512
Angolazione del fascio di luce (1/2 picco):	36°
Colore della custodia:	Argento
Misure:	Larghezza: 26 cm Profondità: 27 cm Altezza: 39 cm
Peso:	2,30 kg
DMX channels:	4/6
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED number:	177
LED type:	10 mm
Beam angle:	36°

Dimensions:	260 x 270 x 390 mm
EUROLITE DMX LED Operator 2 controller	
Piedinatura:	Interno +/-esterno -
Potenza totale installata:	4,00 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore cavo (M) versione da incasso cavo di alimentazione con alimentatore a spina (in dotazione)
Canali DMX:	Uscita 8
Attivazione:	DMX; controllo della musica via microfono
Colore della custodia:	Nero
Colore:	Nero
Struttura della custodia:	Custodia per mixer
Misure:	Larghezza: 26,5 cm Profondità: 16,5 cm Altezza: 5,5 cm
Peso:	1,12 kg
Power supply:	230 V AC, 50 Hz,
	via 12 V DC, 300 mA power unit included in the delivery
DMX512 output:	3-pin XLR connector

OMNITRONIC Cavo XLR 3 poli 5m nero

Struttura cavo:	2 x 0,22 mm ² cavo microfono
Lunghezza cavo:	5 m
Collegamento A:	1 x XLR a 3 poli (M)
Collegamento B:	1 x XLR a 3 poli (F)
Colore:	Nero
Peso:	0,24 kg
Materiale:	Metallo

Contenuto della confezione:

1 x cavi XLR