



L'articolo non è più disponibile.

Features :

Logistica

EUROLITE LED Pixel Mesh 64x64

Modular LED video panel for indoor use

- Bright and colorful projection of videos, animations and graphics
- Ideal for stage/fair construction and fixed installation
- Modular display concept allows the build-up of large areas
- 40 mm pixel pitch (seamless image at about 40 m)
- 16 x 16 pixels
- Transparent design
- Fast and easy setup
- Ethernet-based signal distribution, IEC inputs and outputs
- Controllable via optional network components and PC software
- For operation per 128 panels (256 x 128 pixels), the optional network interface (80503120) and the network control system consisting of sending card and software LED studio (80503130) is required
- Compatible to media software such as MADRIX
- Matching flightcase available
- Delivery includes 1 x IEC cable, 1 x 50 cm RJ45 cable (80503165), 4 x U-connector (80503150), 4 x gasket (80503152), 4 x bolt (80503154), 1 x eye-bolt
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

ROADINGER Flightcase 6x LED Pixel Mesh 64x64

PRO flightcase with castors for 6 x LED Pixel Mesh

- Compartments for 6 LED Pixel Mesh
- High-quality workmanship with 9mm plywood multilayered glued, dark brown laminated
- Cover foldable with strap hinge
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, large steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 butterfly locks
- 2 hinged, chromium plated case handles
- Hardware di marca
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

EUROLITE LED Pixel Mesh 64x64

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	75,00 W
Raffreddamento:	Raffreddamento a convezione passiva
Colore della custodia:	Nero
Misure:	Larghezza: 64 cm Profondità: 6,5 cm Altezza: 64 cm
Peso:	8,55 kg
Power connector:	IEC input and output
Signal connector:	RJ45
Pixel pitch:	40 mm
Pixel configuration:	2 red, 1 blue, 1 green
Module resolution:	16 x 16
Density (point/m²):	625
Brightness (cd/m²):	1300
Scanning mode:	Static
View angle:	120°
Driving voltage:	4.5-5.5 V
Grey scale:	R256 levels, G256 levels, B256 levels
Frame rate:	>/ 60 fps

ROADINGER Flightcase 6x LED Pixel Mesh 64x64

Carico massimo:	100 kg
Uso del marchio:	Hardware di marca
Misure:	Larghezza: 138 cm Profondità: 39 cm Altezza: 88 cm
Peso:	40,40 kg
Outside dimensions (L x W x H):	1380 x 390 x 880 mm

Contenuto della confezione:
