



Features :

Logistica

OMNITRONIC ADI-004M Interface

USB audio interface with integrated low-noise microphone preamplifiers

- Plug & play audio interface connects microphones, instruments and line signals with your computer for recording and playback
- Compatible with PC and Mac - no setup required
- High-resolution AD/DA converters (16 bits/ 44.1 kHz and 48 kHz) for high-end audio quality
- High-speed USB 2.0 support
- 2 microphone/hi-Z instrument inputs (combination XLR/6.3 mm jack, bal.), switchable
- +48 V phantom power can be switched on, status LED
- Line input (stereo RCA)
- Analog inputs with gain control and signal/clip LED
- Digital S/PDIF input and output (RCA)
- Monitoring of input and output via adjustable stereo headphones output (3.5 mm jack (1/8"))
- Adjustable stereo line output (6.3 mm jack, bal.) for PA applications
- Power supply via USB, supplied 9 V power unit or 9 V block battery
- The interface can also be used without a computer e.g. as an independent microphone preamplifier for direct monitoring
- Incl. USB cable
- Works with any customary software for PC and Mac
- Funzionamento a pila/batteria ricaricabile possibile

OMNITRONIC VM-220 S PRO Vocal microphone

Universal dynamic microphone

- Versatile dynamic microphone with cardioid characteristic
- Ideal for song transmission or instrument controlling
- Well-balanced frequency range for natural sound
- Handles high volumes without distortion
- Effective low frequency proximity effect due to flat top grille
- Low-wear reed switch, silent during operation
- Robust diecast body and solid steel basket, applicable for touring
- Delivery includes XLR/jack cable

Dati tecnici :

Peso:	1,15 kg
-------	---------

OMNITRONIC ADI-004M Interface

Potenza totale installata:	6,00 W
----------------------------	--------

Pila:	1 x Blocco E 9,0 V 6F22 zinco-carbone presente
-------	--

Misure:	Larghezza: 14,4 cm Profondità: 12,7 cm Altezza: 5 cm
---------	--

Peso:	0,65 kg
-------	---------

Power supply:	9 V AC/DC, 150 mA
---------------	-------------------

	via USB port, power unit or battery
--	-------------------------------------

Frequency range:	20-20000 Hz, ± 1 dB
------------------	-------------------------

THD:	<0.01 %
------	---------

S/N ratio:	90 dB
------------	-------

Input impedance:	1 kohms (mic), 40 kohms (hi-Z)
------------------	--------------------------------

Maximum gain:	48 dB
---------------	-------

Inputs:	2 x hi-Z/mic (combination XLR/6.3 mm jack, bal.), 1 x line (stereo RCA), S/PDIF (RCA)
---------	--

Outputs:	1 x line L/R (6.3 mm jack, bal.), headphones (3.5 mm stereo jack), S/PDIF (RCA), USB (type B)
----------	---

AD/DA converter:	16 bits
------------------	---------

Sampler frequency:	44.1 kHz or 48 kHz
--------------------	--------------------

Required operating system:	Windows 98SE/ME/2000/XP/Vista, Mac OS 9.1/OS X
----------------------------	---

OMNITRONIC VM-220 S PRO Vocal microphone

Tipo di capsula:	Dinamica
------------------	----------

Intervallo di frequenza:	100 - 14000 Hz
--------------------------	----------------

Peso:	0,5 kg
-------	--------

Type:	Dynamic
-------	---------

Directivity pattern:	Cardioid
Impedance:	600 ohms
Sensitivity:	-73 dB
Connector:	3-pin XLR, bal.
Cable:	3-pin XLR, bal./6.3 mm jack, unbal.

Contenuto della confezione:
