

OMNITRONIC Set LI-105B + Subwoofer + E-300

Art.n.: 09000399

GTIN:



L'articolo non è più disponibile.

Features :

Logistica

OMNITRONIC LI-105B Wall Speaker black

Altoparlante a banda larga A#152_0_0#, 16 Ohm, 50 W RMS

- Dedicated 1-way system for fixed installation
- 13 cm full-range speaker (5")
- Attractive MDF cabinet 9/15 mm
- Scratch-resistant lacquer surface in black or white
- Movable mounting bracket for ceiling or wall installation
- Steel grille
- Spring clamps for serial connection
- For indoor PA applications
- Con staffa di montaggio orientabile e inclinabile per montaggio a parete e a soffitto con qualsiasi angolazione

OMNITRONIC Subwoofer for Control Systems

Passive subwoofer with crossover, 6.5" woofer, 50 W RMS / 4 ohms

- The completion for your Control system
- Can be used for Control 1, Control 5, Control 100 and Control 200
- Stereo connection via screw connector
- Built-in crossover separates at 300 Hz
- High efficiency

- 16.5 cm woofer (6.5") in bandpass enclosure
- Bass-reflex tube with a diameter of 6 cm

OMNITRONIC E-300 MK2 Amplifier

Stereo PA amplifier with limiter, 2 x 150 W/4 ohms

- 2 operating modes can be selected (stereo or bridged) with LED indicators
- Limiter, switchable
- Speaker switch-on delay
- 2 level controls
- Each channel with LED for activated protective circuit (protect) and 7-fold output meter with clip LED
- Complete protection set against short-circuit, overheat, DC voltage, power on/off transients
- Groundlift switch against humming
- Fan cooling
- Signal inputs via XLR or RCA jacks, with XLR feed-through output
- Speaker outputs via lockable Speaker jacks and pairs of screw terminals
- Additional Speaker plug for 8-ohm bridge operation
- Rack installation with 2 units
- Montaggio su rack (19") 48,3 cm

Dati tecnici :

Peso:	22,55 kg
-------	----------

OMNITRONIC LI-105B Wall Speaker black

Capacità di carico:	Programma: 100W Nominale: 50W RMS
Intervallo di frequenza:	150 - 20000 Hz
Sensibilità:	93 dB
Pressione acustica massima:	110 dB
Direzionalità:	100° x 100°
Impedenza:	16 Ohm
Sistema di registrazione:	Staffa di montaggio orientabile e inclinabile per montaggio a parete e a soffitto con qualsiasi angolazione
Collegamenti:	Altoparlante via morsetto a molla
Altoparlante:	1 x 5" Woofer
Colore:	Nero
Misure:	Larghezza: 16 cm Profondità: 15 cm Altezza: 16 cm
Peso:	3,30 kg

OMNITRONIC Subwoofer for Control Systems

Capacità di carico:	Programma: 150W Nominale: 50W RMS
Intervallo di frequenza:	50 - 130 Hz

Sensibilità:	85 dB (1W/1m)
Pressione acustica massima:	91 dB
Collegamenti:	Ingresso: Altoparlante via morsetto a molla
Altoparlante:	1 x 6.5" Woofer
Colore:	Nero
Misure:	Larghezza: 35 cm Profondità: 42 cm Altezza: 25 cm
Peso:	9 kg
Components:	16.5 cm woofer (6.5")
Connection:	stereo / 2-pole terminals
Sensitivity:	85 dB
Maximum SPL:	91 dB

OMNITRONIC E-300 MK2 Amplifier

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	1891,00 W
Potenza in uscita:	100 W RMS (8 Ohm)
Commutazione:	Class AB
Struttura della custodia:	Montaggio su rack (19") 48,3 cm
Misure:	Larghezza: 48,3 cm Profondità: 34,5 cm Altezza: 8,9 cm
Peso:	6,95 kg
Power output sine:	
Stereo 4 ohms	2 x 150 W
8 ohms bridged	1 x 300 W
Frequency range:	10-50000 Hz, ±1.5 dB
Damping factor:	>350
Distortion factor:	0.1 %
Slew rate:	40 V/μsec
S/N ratio:	>90 dB
Channel separation:	>70 dB/ 1 kHz
Input sensitivity:	0.77 V
Input impedance:	20 kohms
Input voltage:	max. 21 dBV/9V
Input connectors:	2 x XLR, 1 x stereo RCA
Output connectors:	2 x Speaker, 1 x Speaker (bridge), 2 x pairs of screw terminals, 2 x XLR (feed-through output)
Control elements:	power switch, level control per channel, mode switch (stereo/bridged), limiter selector, groundlift selector
LED indicators:	stereo, bridged (globally), protect, and 7-fold output meter with clip LED (per channel)
Protection circuits:	short-circuit, overheat, DC voltage, power on/off transients, softstart

Construction:	steel chassis with aluminum front panel
Dimensions (DxWxH):	345 x 482 x 100 mm (19", 2 U)

Contenuto della confezione: