

PSSO FG-1642 Live mixer

4-group live mixer

Art.n.: 10060725

GTIN: 4026397362282

**Descrizione :**

Professional middle class mixer, appearing in compact dimensions. Applicable for FOH control, monitor mixing, or in demanding recording environments. Substantial routing possibilities with 4 groups and 6 aux sends.

Features :

- Low-noise mic/line mixer, 16 channels
- Applicable for FOH control and monitor mixing
- 70 mm faders
- 8 mono inputs with XLR sockets, +48V phantom power (rear) and balanced line inputs
- 4 stereo inputs
- 4 stereo effect returns
- Insert or direct out for every mono channel
- High pass filter and 4-band EQ for all inputs
- 2 LED indicators per input
- 4 groups for leveling complete signal groups (e.g. drums)
- Mutes for every channel, master and every group
- 6 aux send (2 pre, 2 pre/post, 2 post) per channel for controlling the effects and for monitoring
- Separate master, group, control room and headphones outputs
- Talkback facility
- Precise 14-fold LED meter in subgroups and stereo master
- 4-pin XLR connector for gooseneck lamp
- Rugged metal housing
- Incl. case and gooseneck lamp

Logistica

EAN / GTIN: 4026397362282

Peso : 42,90 kg

Lunghezza : 0.76 m

Larghezza : 0.71 m

Altezza : 0.35 m

Merci volumineuse

Dati tecnici :

Alimentazione elettrica:	115/230 V AC, 50/60 Hz
Potenza totale installata:	75,00 W
Intervallo di frequenza:	20 - 20000 Hz
Misure:	Larghezza: 49 cm Profondità: 57 cm Altezza: 19,5 cm
Peso:	19,85 kg
8 mono	XLR/6.3 mm jack, balanced
8 Inserts	6.3 mm jack, unbalanced
4 stereo	XLR/6.3 mm jack, balanced
4 Aux Return:	6.3 mm stereo jack, balanced
1 Tape In	stereo RCA
Talkback Mic	XLR
Outputs:	
2 Master Out	stereo XLR
2 Master Inserts	6.3 mm jack, unbalanced
1 Control Room	6.3 mm stereo jack, balanced
4 Group Out	6.3 mm jack, unbalanced
6 Aux Send:	6.3 mm jack, balanced
8 Direct Out	6.3 mm jack, unbalanced
1 Tape Out	stereo RCA
Headphones	6.3 mm jack, unbalanced
Mixer:	
Dimensions (W x D x H):	490 x 570 x 195 mm
Dimensions (W x D x H):	483 x 210 x 100 mm

Contenuto della confezione: