

OMNITRONIC LH-070 Active dual DI box XLR

Dual DI box/splitter

Art.n.: 10355070

GTIN: 4026397194937



L'articolo non è più disponibile.

Features :

- Active 2-channel DI box with split mode
- 2 high-impedance XLR signal inputs
- 2 low-impedance XLR outputs
- Switchable to split mode (input 1 routes the signal to both outputs)
- Input sensitivity switchable: +20 dB, 0 dB, -30 dB
- Ground-lift switch eliminates signal interference and ground loop problems
- Phase can be switched
- Hi-cut 10 kHz switchable
- Modern convex housing design with rubber corners for safe positioning
- Stackable
- Cables can be routed under the housing
- Operation with 9 V battery (included)
- Funzionamento a pila/batteria ricaricabile possibile

Logistica

EAN / GTIN: 4026397194937

Peso : 0,75 kg

Lunghezza : 0.23 m

Larghezza : 0.16 m

Altezza : 0.10 m

Dati tecnici :

Pila:	1 x blocco E 9,0 V 6LR61 alcalino-manganese presente
Intervallo di frequenza:	10 - 30000 Hz
Misure:	Larghezza: 15 cm Profondità: 13 cm Altezza: 6 cm
Peso:	0,55 kg

Power supply:	9 V battery
Current consumption:	approx. 65 mA
Battery life:	6-8 hours
Input impedance:	470 kohms
Output impedance:	600 ohms
Maximum output level:	6 dBu
Dynamic range:	>100 dB
Hi cut:	10 kHz
Input connectors:	2 x XLR, bal.
Output connectors:	2 x XLR, bal.
THD:	0.5 %

Contenuto della confezione:
