

OMNITRONIC XO-23B Active crossover

Deviatore di frequenza attivo, stereo a 2 vie e funzionamento mono a 3 vie

Art.n.: 10355626

GTIN: 4026397385380



L'articolo non è più disponibile.

Features :

- 2-way stereo or 3-way mono operation possible
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 45 Hz to 9.5 kHz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low cut switch
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistica

EAN / GTIN: 4026397385380

Peso : 2,45 kg

Lunghezza : 0.54 m

Larghezza : 0.20 m

Altezza : 0.08 m

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	10,00 W
Misure:	Larghezza: 48,3 cm Profondità: 14,7 cm Altezza: 4,45 cm
Peso:	2 kg
Slope:	24 dB / octave
Operation modes:	2-way stereo or 3-way mono

Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/Out connectors:	XLR
S/N ratio:	>100 dB
Xover frequency range:	45-9500 Hz
THD:	0.05%
Crosstalk:	>80 dB, -3 dB
Input gain:	- ~ to + 6 dB
Control range:	- ~ to + 12 dB
Low Cut:	30 Hz, -3 dB
Phase adjustment:	0-180°
Dimensions (W x D x H):	483 x 147 x 46 mm

Contenuto della confezione: