

OMNITRONIC XO-34 Active crossover

High-quality stereo crossover

Art.n.: 10355635

GTIN: 4026397233308



L'articolo non è più disponibile.

Features :

- 2-way/3-way stereo or 4-way mono operation possible
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 450 Hz - 9 kHz switchable to 45 - 900 Hz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low Cut switch
- XLR in and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation

Logistica

EAN / GTIN: 4026397233308

Peso : 2,70 kg

Lunghezza : 0.54 m

Larghezza : 0.20 m

Altezza : 0.08 m

Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 10,00 W

Misure: Larghezza: 48,3 cm
Profondità: 14,7 cm
Altezza: 4,45 cm

Peso: 2,25 kg

Slope: 24 dB / octave

Operation modes: 2/3-way stereo or 4-way mono

Input:	Mono/stereo
Input impedance:	10/20 kohms (unb./bal.)
Output:	Mono/stereo
Output impedance:	300/150 kohms (unb./bal.)
In/Out connectors:	XLR
S/N ratio:	>100 dB
Xover frequency range:	45-9000 Hz
THD:	0.05%
Crosstalk:	>80 dB, -3 dB
Input gain:	-- to +6 dB
Output gain:	-- to +12 dB
Low Cut:	30 Hz, -3 dB
Dimensions (W x D x H):	483 x 147 x 46 mm

Contenuto della confezione:
