

## OMNITRONIC LXO-23 Active Crossover

High-quality active stereo crossover with limiter

Art.n.: 10355640

GTIN: 4026397433654



### Features :

- 2-way stereo or 3-way mono operation possible
- Limiter adjustable from -40 to 22 dB
- 24 dB octave slope
- Crossover frequency control on the front panel
- Frequency range of crossover frequency 450 Hz - 9 kHz switchable to 45 - 900 Hz
- Individual output level controls for all bands
- Individual output mutes for easy band adjustment
- Phase invert control
- Low cut switch
- XLR inputs and outputs
- Illuminated switches for secure operation in dark environments
- Rack installation
- Montaggio su rack (19") 48,3 cm 1 U

### Logistica

EAN / GTIN: 4026397433654

Peso : 2,65 kg

Lunghezza : 0.54 m

Larghezza : 0.20 m

Altezza : 0.08 m

### Dati tecnici :

|                            |                                                                                                                                                        |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alimentazione elettrica:   | 230 V AC, 50 Hz                                                                                                                                        |
| Potenza totale installata: | 10,00 W                                                                                                                                                |
| Allacciamento elettrico:   | Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione) |
| Intervallo di frequenza:   | 45 - 9000 Hz                                                                                                                                           |

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Struttura della custodia: | Montaggio su rack (19") 48,3 cm 1 U                           |
| Misure:                   | Larghezza: 48,3 cm<br>Profondità: 14,7 cm<br>Altezza: 4,45 cm |
| Peso:                     | 2,30 kg                                                       |
| Limiter:                  | -40-22 dBu                                                    |
| Slope:                    | 24 dB / octave                                                |
| Operation modes:          | 2-way stereo or 3-way mono                                    |
| Input:                    | Mono/stereo                                                   |
| Input impedance:          | 10/20 kohms (unb./bal.)                                       |
| Output:                   | Mono/stereo                                                   |
| Output impedance:         | 300/150 kohms (unb./bal.)                                     |
| In/Out connectors:        | XLR                                                           |
| S/N ratio:                | >100 dB                                                       |
| THD:                      | 0.05%                                                         |
| Crosstalk:                | >80 dB, -3 dB                                                 |
| Input gain:               | -- to +6 dB                                                   |
| Output gain:              | -- to +12 dB                                                  |
| Low Cut:                  | 30 Hz, -3 dB                                                  |
| Phase adjustment:         | 0-180°                                                        |

#### Contenuto della confezione: