# OMNITRONIC AM-21 Sonic maximizer

Maximize your sound with the sound enhancement system AM-21!

**Art.n.: 10355705**

GTIN: 4026397306231





## L'articolo non è più disponibile.

### Descrizione :

Maximize your sound with the sound enhancement system AM-21!
The AM-21 is a professional sound enhancement processor consisting of a dedicated Sonic Maximizer with an independent noise reduction system in a single rack-space unit. The AM-21 corrects the usual major phase and amplitude distortions that occur when sound is reproduced by a speaker system. The AM-21 improves your sound material dramatically and gives your music the additional dimension you've been looking for. It provides a better dynamic to sound, increases clarity, adds detail and definition. This processor is the perfect sound improvement tool for recording studios, DJ systems, clubs and instrument racks.

### Features :

- Effective sound enhancement system with sonic maximizer and 2-channel noise reduction
- Improves the performance of your sound dramatically by adding clarity, dimension and depth
- Produces high-end transparency and super-tight bass
- Separate bass and definition control and bypass switch on the sonic maximizer section
- Independent section for noise reduction with threshold, release and level control per channel
- Bypass switch allows instant comparison of original sound with processed sound per channel
- Precise 7-digit LED meter with clip LED for output level per channel
- Inputs and outputs via balanced XLR connectors and 6.3 mm jack connectors
- Rack installation, 1 U

### Dati tecnici :

| | |
|---|---|
| Alimentazione elettrica: | 230 V AC, 50 Hz |

### Logistica

EAN / GTIN: 4026397306231
Peso : 2,50 kg
Lunghezza : 0.55 m
Larghezza : 0.20 m
Altezza : 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

| | |
|---|---|
| Potenza totale installata: | 10 W |
| Intervallo di frequenza: | 20 - 20000 Hz |
| Rapporto segnale-rumore: | >90 dB |
| Distorsione armonica totale: | <0,05 % a 1 kHz |
| Misure: | Larghezza: 48,3 cm<br>Profondità: 12 cm<br>Altezza: 4,45 cm |
| Peso: | 2 kg |
| S/N ratio: | >90 dB |
| THD: | 0.05% |
| Crosstalk: | >80 dB, -3 dB |
| Bass definition: | 0 to +9 dB |
| Input impedance: | 10/20 kohms (unbal./bal.) |
| Output impedance: | 300/150 ohms (unbal./bal.) |
| Connection: | 6.3 mm jack (unbal.), 3-pin XLR (bal.) |
| Dimensions (W x D x H): | 483 x 120 x 46 mm |

## Contenuto della confezione:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.