

## OMNITRONIC SD-28 Signal Distributor

8-way signal distributor

Art.n.: 10355735

GTIN: 4026397439359



## L'articolo non è più disponibile.

### Descrizione :

This little and maybe even a bit mousy looking box, which demands one height unit only, is truly an effective signal distributor, which splits 2 input signals to 4 in stereo mode and spreads 1 input signal to 8 exits in mono mode. As the SD-28 is intended to be used for permanent installation, the particular level regulator has been recessed, to avoid a deliberate or accidental change of settings. The tuning of channels is, by the way, supported by clear LED-meters and therefore facilitated. Additionally, another SD-28 can be connected to improve its field of application. This system control distributor is best used for club installments or for multi stacked amplifiers.

### Features :

- Dedicated 2-channel signal distributor with selectable operating mode
- Stereo mode: 2 line input signals to 4 outputs each
- Mono mode: 1 line input signal to 8 outputs
- Each input with 1 parallel output for feeding through the input signal
- Each output with recessed level control (avoids unintended adjustments)
- Precise 7-digit LED meters with clip LED for input level
- Inputs and outputs via balanced XLR connectors
- Rack installation, 1 U
- Montaggio su rack (19") 48,3 cm 1 U

### Dati tecnici :

Alimentazione elettrica:

230 V AC, 50 Hz

### Logistica

EAN / GTIN: 4026397439359

Peso : 2,40 kg

Lunghezza : 0.54 m

Larghezza : 0.25 m

Altezza : 0.09 m

|                            |                                                                                                                                                        |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Potenza totale installata: | 10,00 W                                                                                                                                                |
| Allacciamento elettrico:   | Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione) |
| Intervallo di frequenza:   | 20 - 20000 Hz                                                                                                                                          |
| Struttura della custodia:  | Montaggio su rack (19") 48,3 cm 1 U                                                                                                                    |
| Misure:                    | Larghezza: 48,3 cm<br>Profondità: 12 cm<br>Altezza: 4,45 cm                                                                                            |
| Peso:                      | 2,05 kg                                                                                                                                                |
| S/N ratio:                 | >90 dB                                                                                                                                                 |
| THD:                       | 0.05 %                                                                                                                                                 |
| Crosstalk:                 | >80 dB, -3 dB                                                                                                                                          |
| Gain:                      | ~- to +6 dB                                                                                                                                            |
| Input impedance:           | 20 kohms                                                                                                                                               |
| Output impedance:          | 150 ohms                                                                                                                                               |
| Connection:                | 3-pin XLR (bal.)                                                                                                                                       |

#### **Contenuto della confezione:**