

## OMNITRONIC ADI-004M Interface

USB audio interface with integrated low-noise microphone preamplifiers

Art.n.: 10359840

GTIN: 4026397337891



**L'articolo non è più disponibile.**

### Features :

- Plug & play audio interface connects microphones, instruments and line signals with your computer for recording and playback
- Compatible with PC and Mac - no setup required
- High-resolution AD/DA converters (16 bits/ 44.1 kHz and 48 kHz) for high-end audio quality
- High-speed USB 2.0 support
- 2 microphone/hi-Z instrument inputs (combination XLR/6.3 mm jack, bal.), switchable
- +48 V phantom power can be switched on, status LED
- Line input (stereo RCA)
- Analog inputs with gain control and signal/clip LED
- Digital S/PDIF input and output (RCA)
- Monitoring of input and output via adjustable stereo headphones output (3.5 mm jack (1/8"))
- Adjustable stereo line output (6.3 mm jack, bal.) for PA applications
- Power supply via USB, supplied 9 V power unit or 9 V block battery
- The interface can also be used without a computer e.g. as an independent microphone preamplifier for direct monitoring
- Incl. USB cable
- Works with any customary software for PC and Mac
- Funzionamento a pila/batteria ricaricabile possibile

### Logistica

EAN / GTIN: 4026397337891

Peso : 0,80 kg

Lunghezza : 0.23 m

Larghezza : 0.15 m

Altezza : 0.09 m

### Dati tecnici :

|                            |                                                |
|----------------------------|------------------------------------------------|
| Potenza totale installata: | 6,00 W                                         |
| Pila:                      | 1 x Blocco E 9,0 V 6F22 zinco-carbone presente |
| Misure:                    | Larghezza: 14,4 cm                             |

|                            |                                                                                               |
|----------------------------|-----------------------------------------------------------------------------------------------|
|                            | Profondità: 12,7 cm<br>Altezza: 5 cm                                                          |
| Peso:                      | 0,65 kg                                                                                       |
| Power supply:              | 9 V AC/DC, 150 mA                                                                             |
|                            | via USB port, power unit or battery                                                           |
| Frequency range:           | 20-20000 Hz, $\pm 1$ dB                                                                       |
| THD:                       | <0.01 %                                                                                       |
| S/N ratio:                 | 90 dB                                                                                         |
| Input impedance:           | 1 kohms (mic), 40 kohms (hi-Z)                                                                |
| Maximum gain:              | 48 dB                                                                                         |
| Inputs:                    | 2 x hi-Z/mic (combination XLR/6.3 mm jack, bal.),<br>1 x line (stereo RCA), S/PDIF (RCA)      |
| Outputs:                   | 1 x line L/R (6.3 mm jack, bal.), headphones (3.5 mm stereo jack), S/PDIF (RCA), USB (type B) |
| AD/DA converter:           | 16 bits                                                                                       |
| Sampler frequency:         | 44.1 kHz or 48 kHz                                                                            |
| Required operating system: | Windows 98SE/ME/2000/XP/Vista, Mac OS 9.1/OS X                                                |

### **Contenuto della confezione:**