

HSP-2800 MK2 SMPS Amplifier

Amplificatore PA stereo in class H con alimentatore switching, 2 x 850 W RMS (8 Ohm), 2 x 1400 W RMS (4 Ohm)

Art.n.: 10451690

GTIN: 4026397505917



HSP-2800 MK2 SMPS Amplifier

Amplificatore PA stereo in class H con alimentatore switching, 2 x 850 W RMS (8 Ohm), 2 x 1400 W RMS (4 Ohm)

Art.n.: 10451690

GTIN: 4026397505917

Features :

- Stereo PA amplifier with class H circuitry
- Low weight and height due to integrated switch mode power supply
- Reliable power amp with high impulse stability for a wide range of applications (e.g. compact PAs, multi-way PAs, international concerts)
- Limiter and speaker switch-on delay
- 3 operating modes can be selected (stereo, parallel or bridged)
- 2 calibrated level controls for precise level adjustment
- Input sensitivity and limiter adjustable
- LED VU meter and LEDs for activated protective circuit (protect), overload (clip), and signal per channel
- LEDs for parallel and bridge mode
- Complete protection set against short-circuit, overheat, clipping, overload, DC voltage and VHF signals
- Highly efficient front-to-rear air routing
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs