

## OMNITRONIC AS-360 Active system

Active complete system, 360 W RMS

Art.n.: 11038802

GTIN: 4026397357493



### Features :

- Two-way satellite system consisting of two tops and one subwoofer
- Perfectly tuned system for demanding home users, DJs, musicians, small parties etc.
- Easy-to-use complete system
- Rugged full-range top speaker in a stable wooden housing
- Tops: with passive 2-way crossover
- Sub: powerful, dry bass via optimized double vented bandpass system
- Balanced frequency range with high sound pressure
- Speaker connection via lockable Speaker-plugs
- Scratch-resistant lacquer surface
- Compact speaker system for car transport

### Logistica

EAN / GTIN: 4026397357493

Peso : 29,20 kg

Lunghezza : 0.48 m

Larghezza : 0.41 m

Altezza : 0.64 m

### Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 500,00 W

Potenza in uscita: Massimo 360 W

Intervallo di frequenza: 120 - 20000 Hz

Misure: Larghezza: 35 cm  
Profondità: 14,5 cm  
Altezza: 17 cm

Peso: 26,65 kg

Top:

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Rated power:                    | 120 W RMS                                     |
| Program power:                  | 180 W                                         |
| Components:                     | 2 x 10 cm woofer (2 x 4"), dome tweeter       |
| Connection:                     | 1 Speaker socket                              |
| Sensitivity:                    | 90 dB                                         |
| Maximum SPL:                    | 108 dB                                        |
| Impedance:                      | 4 ohms                                        |
| Dispersion angle:               | 60° x 60°                                     |
| Crossover frequency:            | 3 kHz                                         |
| Dimensions (H x W x D):         | 350 x 145 x 170 mm                            |
| Subwoofer:                      |                                               |
| Rated power:                    | 140 W RMS                                     |
| Program power:                  | 200 W                                         |
| Components:                     | 20 cm woofer (8")                             |
| Sensitivity:                    | 96 dB                                         |
| Maximum SPL:                    | 114 dB                                        |
| Impedance:                      | 4 ohms                                        |
| Dimensions (H x W x D):         | 430 x 320 x 420 mm                            |
| Amplifier:                      |                                               |
| Total power output:             | 360 W RMS                                     |
| Nominal power output satellite: | 2 x 120 W RMS                                 |
| Nominal power output subwoofer: | 120 W RMS                                     |
| Active crossover:               |                                               |
| Crossover frequency:            | 140 Hz                                        |
| Inputs:                         | 2 x XLR, 2 x RCA                              |
| Outputs:                        | 2 Speaker sockets                             |
| Min. input sensitivity:         | 0.350 V                                       |
| Control elements:               | Power switch, Gain control , Sublevel control |
| LED indicators (per channel):   | Power                                         |
| Protection circuits:            | Short-circuit                                 |

## Contenuto della confezione: