

OMNITRONIC PAS-215PRO-A 2-Way Top, active, DSP

Active 2-way PA speaker system with DSP

Art.n.: 11039447

GTIN: 4026397531282



L'articolo non è più disponibile.

Features :

- Active 2-way speaker system for touring applications and permanent installations
- Class D circuitry with switch-mode power supply and 900 watts peak power
- DSP with 5 EQ presets and status display window
- Rugged full-range top speaker qualified for suspended installation and flange for stand installation
- Rotatable constant directivity horn (asymmetrical) with coil driver
- 38 cm woofer in bassreflex cabinet provides powerful, dry bass
- Power, signal and limiter indication
- Adjustable line input, combination XLR/6.3 mm jack and RCA
- Adjustable microphone input, combination XLR/6.3 mm jack; switchable to line
- Line output (XLR) for linking further active speaker systems
- Optimized for combination with PAS subwoofers
- Impact-resistant steel grille with acoustic foam
- Trapezoidal, multilayered glued plywood housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport

Logistica

EAN / GTIN: 4026397531282

Peso : 24,25 kg

Lunghezza : 0.45 m

Larghezza : 0.51 m

Altezza : 0.78 m

Dati tecnici :

Alimentazione elettrica: 100-240 V AC, 50/60 Hz

Intervallo di frequenza: 50 - 20000 Hz

Altoparlante: 1 x 15" Woofer

Misure: Larghezza: 43 cm

	Profondità: 36,5 cm Altezza: 70 cm
Power consumption:	110 W (1/8 power)
Rated power:	450 W RMS
Program power:	900 W
Components:	38 cm woofer (15"), 4.5 cm horn (1.75")
Input:	
Line:	Combination XLR/6.3 mm jack, RCA L/R
Mic:	Combination XLR/6.3 mm jack
Output:	
Line:	XLR
Sensitivity:	97 dB
Maximum SPL:	124 dB
Impedance:	8 ohms
Crossover frequency:	2 kHz
Dispersion angle:	50-100° x 55°
Weight:	22 kg

Contenuto della confezione: