

PSSO K-215SE 2-Way Top 600W

PRO PA speaker, 15" woofer, 1.5" horn, 600 W RMS, 8 ohms

Art.n.: 11041109

GTIN: 4026397545401



L'articolo non è più disponibile.

Features :

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter with titanium diaphragm
- Horn exit 38 mm (1.5")
- Voice coil 72 mm (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Dual-angle-Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- Driver di CELTO ACOUSTIQUE
- Collegamento a innesto NEUTRIK installato
- Realizzato in europa

Logistica

EAN / GTIN: 4026397545401

Peso : 32,45 kg

Lunghezza : 0.51 m

Larghezza : 0.49 m

Altezza : 0.79 m

Merci voluminose

Dati tecnici :

Capacità di carico:	Programma: 1200W
	Nominale: 600W RMS

Intervallo di frequenza:	47 - 19000 Hz
--------------------------	---------------

Sensibilità:	99 dB (1W/1m)
--------------	---------------

Pressione acustica massima:	127 dB
Direzionalità:	80° x 50°
Impedenza:	8 Ohm
Collegamenti:	Ingresso: Altoparlante via 2 x SpeakON a 2 poli (F) versione da incasso
Frequenza di taglio:	1500 Hz
Altoparlante:	1 x 15" Woofer 1 x 1.35" Tromba
Tipo di altoparlante:	Cassa compatta
Uso del marchio:	Driver di CELTO ACOUSTIQUE Collegamento a innesto NEUTRIK installato
Misure:	Larghezza: 44,5 cm Profondità: 41,5 cm Altezza: 71 cm
Peso:	29,45 kg

Contenuto della confezione:

1 x testata
1 x Manuale d'uso