OMNITRONIC MMC-1 USB audio controller

PRO USB MIDI controller for controlling DJ software

Art.n.: 11045020

GTIN: 4026397352580











L'articolo non è più disponibile.

Features :

- DJ controller for playing, mixing, manipulating and scratching music from computers
- Windows XP/Vista and Mac OS X compatible
- MIDI controller with 58 buttons, 7 encoders, 9 controls, 5 faders and crossfader
- All MIDI controllers can be edited and freely assigned
- 6-channel sound card, configurable to: 2 separate stereo outputs or mixed signal to 1 stereo output
- ASIO compatible for ultra-low latency and best audio quality
- Operation via supplied switch mode power unit
- Rack installation, 3 U
- The complete solution for computer DJs: dual player and mixer with FX section
- 2-channel mixer section:
- 3-band EQ, channel fader per channel
- FX unit with adjustable X and Y parameters per channel
- Replaceable crossfader
- Master control
- Prefader listening
- Track encoder
- Dual player section:
- 2 jog dials with scratch function
- Pitch fader
- Pitch Bend buttons
- Snyc function (autom. beat matching)
- Seamless loop/reloop function
- Auto loop
- 4 cue hotkeys
- 4 sampler buttons

Logistica

EAN / GTIN: 4026397352580

Peso : 2,90 kg

Lunghezza : 0.59 m

Larghezza : 0.20 m

Altezza : 0.14 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

- Faderstart function

Dati tecnici :

Potenza totale installata:	9,00 W
Intervallo di frequenza:	20 - 20000 Hz
Misure:	Larghezza: 48,3 cm Profondità: 7,5 cm Altezza: 13,35 cm
Power supply:	230 V AC, 50 Hz,
	via supplied power unit 6 V DC, 3.5 A
Type:	USB MIDI controller
Distortion:	0.008 %
S/N ratio:	95 dB
Channel separation:	95 dB
Audio output:	2 x RCA, unbalanced
Output voltage:	2 V/ 100 kohms
Headphones output:	6.3 mm stereo jack
Output voltage:	1.6 V/ 32 ohms
Fader start output:	2 x 3.5 mm jack (1/8")
USB ports (type A):	2.0, downward compatible
Tone control:	
2 x High:	-20 dB to +9 dB/ 10 kHz
2 x Middle:	-19 dB to +9 dB/ 1 kHz
2 x Low:	-16 dB to +9 dB/ 100 Hz
Dimensions:	483 x 74,8 x 132 mm
	Rack installation, 3 U
Weight:	2.1 kg
Minimum system requirements PC:	
	Windows XP/Vista
	1.6 GHz processor
	512 MB RAM
	DirectSound or ASIO compatible sound card
	USB port Anschluss (min. USB 1.1)
Minimum system requirements Mac:	
	Mac OS X 10.4
	1.25 GHz CPU processor
	512 MB RAM
	Sound card with CoreAudio drivers
	USB port (min. USB 1.1)

Contenuto della confezione:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.