

## OMNITRONIC DSM-700 Micropophone set

Complete drum microphone set

Art.n.: 13030450

GTIN: 4026397174113



**L'articolo non è più disponibile.**

### Features :

- Set consisting of one dyn. kick drum microphone KDM-500, three dyn. bass drum microphones BDM-500 (for snare or toms), one dyn. microphone IM-550 and two IM-500 electret microphones (incl. two windshields)
- Rugged microphones with cardioid characteristics for studio and stage use
- All microphones with bal. XLR output and stand holders with 1 cm (3/8") and 1.5 cm (5/8") thread
- Delivery includes padded flightcase, black laminated with aluminum profile frames
- Excellent quality at a low price

### Logistica

EAN / GTIN: 4026397174113

Peso : 4,50 kg

Lunghezza : 0.39 m

Larghezza : 0.31 m

Altezza : 0.10 m

### Dati tecnici :

|                          |                      |
|--------------------------|----------------------|
| Intervallo di frequenza: | 20 - 10000 Hz        |
| KDM-500:                 |                      |
| Type:                    | Dynamic              |
| Directivity pattern:     | Cardioid             |
| Impedance:               | 150 ohms             |
| Sensitivity:             | -58 dB ( $\pm 3$ dB) |
| Weight:                  | 450 g                |
| BDM-500:                 |                      |
| Type:                    | Dynamic              |

|                      |                           |
|----------------------|---------------------------|
| Directivity pattern: | Cardioid                  |
| Impedance:           | 250 ohms                  |
| Sensitivity:         | -54 dB (±3 dB)            |
| Weight:              | 200 g                     |
| IM-500:              |                           |
| Type:                | Condenser (back electret) |
| Directivity pattern: | Cardioid                  |
| Impedance:           | 200 ohms                  |
| Sensitivity:         | -45 dB (±3 dB)            |
| Maximum SPL:         | 136 dB                    |
| S/N ratio:           | >60 dB                    |
| Phantom power:       | 9-52 V DC, 2.0 mA         |
| Weight:              | 200 g                     |
| IM-550:              |                           |
| Type:                | Dynamic                   |
| Directivity pattern: | Cardioid                  |
| Impedance:           | 250 ohms                  |
| Sensitivity:         | -54 dB (±3 dB)            |
| Weight:              | 200 g                     |

**Contenuto della confezione:**

---