

OMNITRONIC GS-100 UHF wireless guitar set

UHF wireless guitar system

Art.n.: 13053501

GTIN: 4026397325331



L'articolo non è più disponibile.

Features :

- Set includes receiver and mini-transmitter
- The GS-100 guitar system replaces the cable between guitar and stage amplifier or mixer, providing unparalleled freedom of movement on stage
- Receiver:
 - Diversity system with folding antennas
 - Operation in the low-interference UHF band (863-865 MHz)
 - Balanced XLR output and unbal. 6.3 mm output
 - Adjustable squelch and output level
 - LED indicators for antenna A/B, audio signal and peak
- Incl. jack-jack cable for connecting the receiver to an audio mixer
- Operation via supplied power unit
- Mini-transmitter:
 - Lightweight and aerodynamic design with 6.3 mm jack
 - Switchable input attenuation: 0 dB, -0 dB
 - LED indicator for battery capacity
- Operation via supplied micro battery (type AAA)
- License-free and approved in the EU
- Funzionamento a pila/batteria ricaricabile possibile

Logistica

EAN / GTIN: 4026397325331

Peso : 1,90 kg

Lunghezza : 0.43 m

Larghezza : 0.10 m

Altezza : 0.31 m

Dati tecnici :

Potenza totale installata:	5,00 W
Pila:	1 x Micro (AAA) (non in dotazione)
Misure:	Larghezza: 23,5 cm

	Profondità: 11,8 cm Altezza: 4,4 cm
Peso:	1,70 kg
Carrier frequency:	UHF 863.900 MHz
Coverage:	50 m (with line-of-sight)
Frequency range:	60-16000 Hz (± 3 dB)
T.H.D.:	<1 %
Dynamic range:	90 dBA
Receiver:	
System:	Diversity, 1 channel
Max. audio output level:	-18 dBV/ 3000 ohms (6.3 mm jack) -12 dBV/ 600 ohms (XLR)
Output impedance:	1 kohms (6.3 mm jack) 200 ohms (XLR)
Sensitivity:	<-92 dB
Power supply:	12-18 V DC, 400 mA (receiver) 230 V AC, 50 Hz (power supply unit)
Micro-transmitter:	
RF power output:	<10 mW
Frequency range:	50-20000 Hz
T.H.D.:	<1 %
Dynamic range:	90 dBA
S/N ratio:	<102 dBV
Max. audio input level:	10 dBV
Gain adjustment range:	30 dB
Input impedance:	500 kohms
Dimensions (H x W x D):	76 x 20 x 28 mm

Contenuto della confezione: