

OMNITRONIC UHF-502 2-Channel Wireless Mic System 863-865 MHz

Sistema microfonico a 2 canali in tecnologia UHF-PLL

Art.n.: 13053530

GTIN: 4026397603989



L'articolo non è più disponibile.

Features :

- 2-channel multifrequency receiver unit and 2 hand-held microphones with UHF PLL technology
- 80 fixed frequencies selectable per channel
- Pilot tone technology (PLL) and noise squelch for interference-free operation
- Automatic frequency scan (AFS) finds interference-free channels
- Easy and error-free synchronization between receiver and transmitters via infrared signal
- LCDs for RF reception level, AF audio level, frequency and channel
- Parallel operation of up to 4 transmission channels is possible without any interference
- Lock function avoids accidental changing of the transmission channel
- 2 separate channels with volume controls
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output, switchable mic/line
- Jack cable included
- Non-diversity system with two removable antennas (BNC connection)
- Microphones with mute switch and color caps for distinction on stage
- Operation of the receiver unit via supplied power unit
- Operation of the microphones via 2 x 1.5 V batteries (type AA), not included
- Receiver unit with aluminum front panel and dimensions for 483 mm rack installation (1U)
- License-free and approved in the EU
- Direttività: Cardioide
- Portata fino a 50m a vista
- UHF 863 - 865 MHz registrazione e gratuità in Europa
- Montaggio su rack (19") 48,3 cm

Logistica

EAN / GTIN: 4026397603989

Peso : 3,00 kg

Lunghezza : 0.51 m

Larghezza : 0.39 m

Altezza : 0.08 m

Dati tecnici :

Tipo:	Set senza fili completo
Potenza totale installata:	5 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore cavo (M) versione da incasso cavo di alimentazione con alimentatore a spina (in dotazione)
Tipo di capsula:	Dinamica
Direttività:	Cardioide
Intervallo di frequenza:	40 - 18000 Hz
Rapporto segnale-rumore:	>80 dB
Sensibilità:	-95 dB
Massima:	Fino a 50m a vista
Banda di frequenza:	UHF 863 - 865 MHz
Selezione frequenza:	Frequenze commutabili
Materiale:	Metallo
Struttura della custodia:	Montaggio su rack (19") 48,3 cm
Peso:	2,46 kg
Pila:	4 x Mignon (AA) (non in dotazione)
Interruttore:	Interruttori di accensione/spegnimento; interruttore silenzioso
Peso:	0,230 kg
Misure:	Larghezza: 48,3 cm Profondità: 25,3 cm Altezza: 4,45 cm
Peso:	1,9 kg
System:	Non-diversity, 2 channels
Color code:	CH A = red, CH B = blue
Receiving frequencies:	80
RF power output:	10 mW
Modulation method:	FM
Frequency stability:	10 ppm
Selectivity:	>80 dB
T.H.D.:	<0.1 %
Audio outputs:	
Mic:	2 x XLR, bal.
Mix:	6.3 mm jack, unbal.
Power supply:	
Receiver:	12 V DC via supplied power unit (100-240 V AC, 50/60 Hz)
Dimensions, weight:	
Microphones:	50 x 240 mm (D x L), 230 g (w/o batteries)

Contenuto della confezione:

1 x microfono

1 x ricevitore