

OMNITRONIC UHF-502 Bodypack 863-865MHz, incl. Lavalier (CH B blue)

Trasmettitore tascabile con microfono lavalier

Art.n.: 13053532

GTIN: 4026397604184



L'articolo non è più disponibile.

Features :

- Pocket transmitter for UHF-502 microphone system with the same carrier frequency
- Incl. lavalier microphone
- Headset microphone optional
- Pilot tone technology (PLL) for interference-free operation
- Infrared interface for easy and error-free synchronization with the receiver via infrared signal
- LCD for battery capacity and transmission channel
- Sensitivity adjustable
- Transmitting power 5 mW/10 mW, switchable
- LED battery indicator
- Belt clip
- Operation via 2 x 1.5 V batteries (type AA), not included
- License-free and approved in the EU
- Direttività: Cardioide
- UHF 863 - 865 MHz registrazione e gratuità in Europa

Logistica

EAN / GTIN: 4026397604184

Peso : 0,20 kg

Lunghezza : 0.21 m

Larghezza : 0.09 m

Altezza : 0.07 m

Dati tecnici :

Tipo:	Trasmettitore tascabile con microfono
Tipo di capsula:	Condensatore
Direttività:	Cardioide
Pila:	2 x Mignon (AA) (non in dotazione)
Intervallo di frequenza:	50 - 15000 Hz

Banda di frequenza:	UHF 863 - 865 MHz
Selezione frequenza:	Frequenze commutabili
Interruttore:	Interruttori di accensione/spegnimento
Misure:	Larghezza: 6,6 cm Profondità: 2,2 cm Altezza: 10,8 cm
Peso:	0,120 kg
Color code:	CH A = red, CH B = blue
Receiving frequencies:	100
Coverage:	50 m (with line-of-sight)
RF power output:	5 mW (LO), 10 mW (HI)
Modulation method:	FM
Frequency stability:	10 ppm
S/N ratio:	>90 dB
T.H.D.:	<1 %
Audio input:	mini XLR (supplies 5 V)
Power consumption:	100 mA (LO), 130 mW (HI)
Lavalier microphone:	
Type:	Electret
Directivity pattern:	Cardioid
Sensitivity:	-47 dB
Impedance:	680 ohms
S/N ratio:	>63 dB
Power supply:	2-10 V DC
Connection:	cable with 3-pin mini XLR plug
Cable length:	approx. 1 m
Capsule:	9.7 x 5.2 mm

Contenuto della confezione: