

## OMNITRONIC TM-1000 MK2 Pocket transmitter

Trasmettitore tascabile con trasmettitore multifrequenza PLL

Art.n.: 13055511

GTIN: 4026397415353



**L'articolo non è più disponibile.**

### Descrizione :

For the rough stage use

The TM-1000 pocket transmitter comes in a rugged metal housing and withstands every rough stage use. A robust case with foam padding is included for save transport.

### Features :

- Multifrequency pocket transmitter with UHF pilot tone technology (PLL)
- Matches receiver DR-1000 MK2
- Suitable for lavalier microphones or headsets with mini XLR plug
- Operation in the low-interference UHF band (740-764 MHz)
- 192 carrier frequencies switchable in 125 kHz steps (40 frequencies per MHz)
- Transmitting power 10 mW, operation range 100 meters
- Multichannel operation with up to 16 pocket transmitters possible
- LCD for battery status and frequency
- Sensitivity adjustable
- Lock function avoids undesired changes by users, also accidental shutdown
- Operation via 2 x 1.5 V mignon battery (type AA), not included
- Can also be used for direct guitar pickup (via optional adapter cable)
- License required in Germany

### Logistica

EAN / GTIN: 4026397415353

Peso : 0,87 kg

Lunghezza : 0.36 m

Larghezza : 0.17 m

Altezza : 0.08 m

### Dati tecnici :

Pila: 2 x 1.5 V AA Mignon LR06 alkaline manganese presente

|                      |                                                              |
|----------------------|--------------------------------------------------------------|
| Banda di frequenza:  | UHF                                                          |
| Misure:              | Larghezza: 19,6 cm<br>Profondità: 10,6 cm<br>Altezza: 7,8 cm |
| Peso:                | 0,64 kg                                                      |
| Antenna:             | Built-in                                                     |
| Carrier frequency:   | UHF 740-764 MHz                                              |
| Switching bandwidth: | 24 MHz                                                       |
| No. of frequencies:  | 192                                                          |
| Frequency steps:     | 125 kHz                                                      |
| Modulation:          | FM                                                           |
| Frequency stability: | ±0.005 %                                                     |
| AF response:         | 40-18000 Hz                                                  |
| RF power output:     | 10 mW                                                        |
| Coverage:            | 100 m (with line-of-sight)                                   |
| Current consumption: | 100 mA                                                       |
| Connection:          | 3-pin mini XLR                                               |

#### **Contenuto della confezione:**