

OMNITRONIC W.A.M.S-04D Wireless PA system

Portable PA system

Art.n.: 13106982

GTIN: 4026397414370



L'articolo non è più disponibile.

Features :

- Portable all-in-one system with amplifier, speaker system, wireless microphone, CD player with pitch adjustment and remote control, tape deck
- Ideal for all mains independent and wireless applications like speeches, conferences, presentations, sales events etc.
- Operation via mains, built-in rechargeable lead gel batteries for up to 4 hours operating time (integrated automatic charging of the batteries) or external 18 V source
- Easy transportation via telescopic trolley handle, 2 wheels and transport handle
- Wireless operation with fixed VHF frequency 202.950 MHz
- Matching pocket transmitter TM-200A optional
- 3 independently adjustable microphone inputs (6.3 mm jack)
- 1 adjustable line input (6.3 mm jack)
- Microphone channels with switchable talkover function and adjustable echo
- Tone control
- Level control for CD/tape
- 1 line output, 1 aux output (both 6.3 mm jack)
- 1 recording output (stereo RCA)
- High-capacity bass reflex speaker system (2 x 20 cm woofer)
- Interconnection of 2 systems possible for stereo operation
- Enclosure with scratch-resistant lacquer surface, impact-resistant steel grille and flange for speaker distance tube
- CD-player: CD-DA, CD-R, CD-RW, WAV, WMA
- Pitch control
- IR remote control
- Anti-shock
- Loop function, random play, repeat functions, title programming
- License required in Germany

Logistica

EAN / GTIN: 4026397414370

Peso : 21,35 kg

Lunghezza : 0.47 m

Larghezza : 0.47 m

Altezza : 0.74 m

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	110,00 W
Intervallo di frequenza:	80 - 13000 Hz
Misure:	Larghezza: 35 cm Profondità: 30 cm Altezza: 57,5 cm
Peso:	17,90 kg
General:	
	or 18 V DC via built-in lead gel rechargeable batteries or external source
Battery type:	3 x 6 V/7 Ah, removable
Battery operation:	2-4 hours
Recharging time:	7-10 hours
Dimensions (H x W x D):	575 x 350 x 300 mm
Amplifier:	
Nominal power output:	60 W RMS/ 4 ohms
Maximum power output:	100 W/ 4 ohms
Min. input sensitivity:	0.775 V
Distortion:	0.5 %
Connection:	
Inputs:	3 x microphone/1 x aux (6.3 mm jack bal./unbal.)
Outputs:	1 x line/1 x aux (6.3 mm jack bal./unbal.), 1 x record (stereo RCA)
Speaker system:	
Rated power:	2 x 30 W RMS
Program power:	100 W
Components:	2 x 20 cm woofer (2 x 8")
Sensitivity:	90 dB
Maximum SPL:	95 dB
Impedance:	4 ohms
Wireless receiver:	
System:	Non-diversity, one channel
Carrier frequency:	VHF 202.950 MHz
Frequency stability:	±0.005 %
S/N ratio:	>60 dB
Input sensitivity:	10 dB
Dynamic range:	>100 dB
Modulation method:	FM
Coverage:	approx. 50 m (with line-of-sight)
CD player:	CD/-R/-RW in CD-DA format

Contenuto della confezione:
