



L'articolo non è più disponibile.

Features :

Logistica

FUTURELIGHT DMH-60 LED Moving Head

High performance LED moving head with 60 W LED

- 1 extra bright 60 W LED for best luminance
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 3D prism and frost filter
- Macro function for rotating gobos/rotating prism combinations
- Color wheel with 8 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Power standby mode
- Automatic position correction
- PAN angle switchable between 630° and 540°

- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Sound-controlled via built-in microphone
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- DMX control via every standard DMX controller
- Può funzionare in modalità 14 CH DMX
- Controllabile via controllo della musica via microfono; DMX; RDM

ROADINGER Flightcase 2x DMH-30/DMH-40

PRO flightcase for 2 x FUTURELIGHT DMH-60/DMH-40/DMH-30 LED moving head

- Developed for 51841836 FUTURELIGHT DMH-60 LED Moving Head, 51841835 FUTURELIGHT DMH-40 LED Moving Head, 51841825 FUTURELIGHT DMH-30 LED Moving Head or comparable Moving Heads
- Suitable for 2 units
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 high-quality butterfly locks
- 2 high-quality plated case handles
- For perfect protection
- Ruote girevoli
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

EUROLITE TPC-10 Morsetto, argento

Morsetto di montaggio per tubo da 50 mm, capacità di carico massima WLL 150 kg

EUROLITE Corda di sicurezza AG-15 4x1000mm fino a 15kg

Corda di sicurezza di alta qualità

- Per la messa in sicurezza di carichi sopra le persone
- Corda a trefoli rotondi 6 x 19 con inserto in fibra
- Con due redance
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Fune con redancia e connettore
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

FUTURELIGHT DMH-60 LED Moving Head

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	245 W
Movimento oscillatorio TILT massimo:	270° posizionamento
Movimento di rotazione PAN massimo:	630° posizionamento
Frequenza di lampeggiamento:	1 - 13 Hz
Gobo:	Diametro esterno 27mm Diametro immagine 22mm

Canali DMX:	14
Attivazione:	Controllo della musica via microfono; DMX; RDM
Fixtures disponibili per:	Light´J
Angolazione del fascio di luce (1/2 picco):	14°
Colore:	Nero
Misure:	Larghezza: 30,1 cm Profondità: 24,7 cm Altezza: 40,6 cm
Peso:	11,40 kg
DMX channels:	14
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	13 Hz
LED type:	60 W, white
LED number:	1
Beam angle:	14°
Color-wheel:	8 dichroic filters plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	301 x 247 x 406 mm

ROADINGER Flightcase 2x DMH-30/DMH-40

Carico massimo:	50 kg
Ausilio di trasporto:	Ruote girevoli
Materiale:	Legno multistrato di betulla, 7 mm
Colore:	Marrone scuro, laminato
Misure:	Larghezza: 72,5 cm Profondità: 40 cm Altezza: 68 cm
Peso:	18,80 kg
Strength:	7 mm
Outside dimensions (W x D x H):	725 x 400 x 680 mm
Inside dimensions (W x D x H):	685 x 360 x 460 mm

EUROLITE TPC-10 Morsetto, argento

Carico massimo BGV C1 (8 volte sup.):	75 kg
Carico massimo WLL (4 volte sup.):	150 kg
Diametro del tubo campo:	48 - 50 mm
Materiale:	Alluminio

Colore:	Argento
Vite di montaggio:	M10
Misure:	Lunghezza: 10 cm Larghezza: 3 cm Profondità: 9 cm
Peso:	0,16 kg

EUROLITE Corda di sicurezza AG-15 4x1000mm fino a 15kg

Carico da assicurare (BGV C1):	Max. 15 kg
Struttura funicolare:	6 x 19 FC
Classe di resistenza della fune:	1770
Norma:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Resistenza nominale della fune:	1770 N/mm ²
Superficie dei fili:	Zincato
Colore:	Argento
Intervallo di temperatura:	-40° C - +100° C
Misure:	Lunghezza: 100 cm Diametro: Ø 0,40 cm
Peso:	0,10 kg
Peso in lunghezza:	0,0554 kg/m

Contenuto della confezione:

1 x Cavo d'arresto
1 x Connettore