



Features :

Logistica

FUTURELIGHT EYE-7 RGBW LED Moving-Head Beam

4in1 moving head beam with 15 W LEDs

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed
- Supports RDM (Remote Device Management)
- 14, 16 or 22 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset

- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

ROADINGER Flightcase 4x EYE-7 RGBW

Custodia per cassa with ruote girevoli

- Compartments for 4 units and accessory
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, large steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 high-quality butterfly locks (w/o locking function)
- 4 hinged, chromium plated case handles
- Ruote girevoli
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

EUROLITE TPC-10 Morsetto, argento

Morsetto di montaggio per tubo da 50 mm, capacità di carico massima WLL 150 kg

EUROLITE Corda di sicurezza AG-15 4x1000mm fino a 15kg

Corda di sicurezza di alta qualità

- Per la messa in sicurezza di carichi sopra le persone
- Corda a trefoli rotondi 6 x 19 con inserto in fibra
- Con due redance
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Fune con redancia e connettore
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

FUTURELIGHT EYE-7 RGBW LED Moving-Head Beam

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	100,00 W
Misure:	Larghezza: 17,9 cm Profondità: 35 cm Altezza: 24,4 cm
DMX channels:	14/16/22
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED number:	7
LED type:	15 W QCL
Beam angle:	7°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°

Dimensions (L x W x H):	244 x 179 x 350 mm
Weight:	6 kg

ROADINGER Flightcase 4x EYE-7 RGBW

Carico massimo:	100 kg
Ausilio di trasporto:	Ruote girevoli
Materiale:	Legno multistrato di betulla, 7 mm
Colore:	Marrone scuro, laminato
Misure:	Larghezza: 66 cm Profondità: 53,5 cm Altezza: 54 cm
Peso:	20,20 kg
Strength:	7 mm
Outside dimensions (W x D x H):	660 x 535 x 540 mm
Inside dimensions (W x D x H):	620 x 490 x 315 mm
Device compartment (W x D x H):	255 x 245 x 280 mm

EUROLITE TPC-10 Morsetto, argento

Carico massimo BGV C1 (8 volte sup.):	75 kg
Carico massimo WLL (4 volte sup.):	150 kg
Diametro del tubo campo:	48 - 50 mm
Materiale:	Alluminio
Colore:	Argento
Vite di montaggio:	M10
Misure:	Lunghezza: 10 cm Larghezza: 3 cm Profondità: 9 cm
Peso:	0,16 kg

EUROLITE Corda di sicurezza AG-15 4x1000mm fino a 15kg

Carico da assicurare (BGV C1):	Max. 15 kg
Struttura funicolare:	6 x 19 FC
Classe di resistenza della fune:	1770
Norma:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Resistenza nominale della fune:	1770 N/mm²
Superficie dei fili:	Zincato
Colore:	Argento
Intervallo di temperatura:	-40° C - +100° C
Misure:	Lunghezza: 100 cm Diametro: Ø 0,40 cm
Peso:	0,10 kg
Peso in lunghezza:	0,0554 kg/m

Contenuto della confezione:

1 x Cavo d'arresto
1 x Connettore