



L'articolo non è più disponibile.

Features :

Logistica

EUROLITE LED TMH-15 Moving Head Zoom Wash

4in1 moving head wash with zoom and 15 W 4in1 RGBW LEDs

- Equipped with seven 15 W quadcolor LEDs with RGBW colors
- Compact lightweight
- Motorized zoom with 11°- 55° beam angle
- Color presets
- Positioning within 630° PAN and 200° TILT
- Stepless RGBW color mixture
- Masterdimmer
- Internal programs
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with graphic LC display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Il dispositivo è raffreddato tramite Ventola

- Controllabile via DMX; stand-alone
- Senza sfarfallio
- With a beam angle of 11° - 55°

ROADINGER Flightcase 4x TMH-15 with wheels

Custodia per cassa with ruote girevoli

- Fitted for 4 devices and accessory
- Additional accessory compartment
- Interior upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, big steel ball corners
- Lid with 2 tip-over locks
- 4 chrome butterfly locks
- 4 chrome case handles
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- Ruote girevoli
- Hardware di marca
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

Peso:	44,60 kg
-------	----------

EUROLITE LED TMH-15 Moving Head Zoom Wash

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	130 W
Tipo di lampada:	Lampada a LED
Raffreddamento:	Ventola
Attivazione:	DMX; stand-alone
Fixtures disponibili per:	Light' J; LED PC-Control 512
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	11° - 55°
Angolazione del fascio di luce (1/2 picco):	11 - 28°
Angolazione del fascio di luce (1/10 di picco):	25 - 55°
Illuminamento in lux (lx):	Eng rosso (R) 3m: 702 lx, 6m: 182 lx Eng verde (G) 3m: 1131 lx, 6m: 298 lx Eng blu (B) 3m: 185 lx, 6m: 50 lx Eng bianco freddo (CW) 3m: 1139 lx, 6m: 304 lx Eng tutti 3m: 2272 lx, 6m: 600 lx Larghezza rosso (R) 3m: 157 lx, 6m: 42 lx Larghezza verde (G) 3m: 238 lx, 6m: 65 lx Larghezza blu (B) 3m: 54 lx, 6m: 15 lx Larghezza bianco freddo (CW) 3m: 329 lx, 6m: 91 lx Larghezza tutti 3m: 562 lx, 6m: 155 lx
Colore della custodia:	Nero
Misure:	Larghezza: 25 cm Profondità: 15 cm

	Altezza: 33,5 cm
Peso:	5,35 kg
DMX channels:	13
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED type:	Cree 15 W QCL
LED number:	7
Maximum PAN-movement:	630°
Maximum TILT-movement:	200°
Beam angle:	11° - 28°
Dimensions (L x W x H):	150 x 250 x 335 mm

ROADINGER Flightcase 4x TMH-15 with wheels

Carico massimo:	100 kg
Ausilio di trasporto:	Ruote girevoli
Uso del marchio:	Hardware di marca
Materiale:	Legno multistrato di betulla, 7 mm
Colore:	Marrone scuro, laminato
Misure:	Larghezza: 76 cm Profondità: 61,5 cm Altezza: 42 cm
Peso:	23,20 kg
Strength:	7 mm
Outside dimensions (W x D x H):	760 x 615 x 420 mm
Compartment dimensions (W x D x H):	125 x 280 x 300 mm
Accessory compartment (W x D x H):	100 x 610 x 320 mm

Contenuto della confezione: