



Features :

Logistica

EUROLITE Audience Blinder 2x100W LED COB 3200K

Audience blinder, wide beam 2 x 100 W COB LED (warm white)

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 2 LED 100 W COB (chip-on-board) bianco caldo (WW)
- Dimmer
- Effetto stroboscopico
- Può funzionare in modalità 1; 2; 4 CH DMX
- Controllabile via DMX
- With a beam angle of 60°

ROADINGER Flightcase 4x Audience Blinder 2xCOB

Custodia per cassa with ruote girevoli

- Compartments for 4 x Audience Blinder and accessory
- Suitable for 41606100 EUROLITE Audience Blinder 2x50W LED COB 3200K and 41606120 EUROLITE Audience Blinder 2x100W LED COB 3200K
- Interior upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chrome)
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- 2 hinges
- 2 high-quality butterfly locks
- 4 high-quality plated case handles
- For perfect protection
- High-quality workmanship with Legno multistrato di betulla 7 mm, marrone scuro, laminato
- Ruote girevoli
- Hardware di marca
- Made in Europe
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

Peso: 41,00 kg

EUROLITE Audience Blinder 2x100W LED COB 3200K

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	260 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x PowerCON (grigio), versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	2 x 100 W COB (chip-on-board) bianco caldo (WW)
Frequenza di lampeggiamento:	1 - 20 Hz
Attrezzature:	Dimmer
Canali DMX:	1; 2; 4
Attivazione:	DMX
Fixtures disponibili per:	Light´J; LED PC-Control 512; Light Captain
Angolazione del fascio di luce:	60°
Angolazione del fascio di luce (1/2 picco):	60°
Temperatura colore:	3200K
Colore della custodia:	Nero
Misure:	Larghezza: 42 cm Profondità: 14 cm Altezza: 24 cm

Peso:	4,50 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	2
LED type:	Array 100 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm

ROADINGER Flightcase 4x Audience Blinder 2xCOB

Carico massimo:	100 kg
Ausilio di trasporto:	Ruote girevoli
Uso del marchio:	Hardware di marca
Materiale:	Legno multistrato di betulla, 7 mm
Colore:	Marrone scuro, laminato
Dimensioni interne:	70 cm x 44 cm x 36 cm
Dimensioni vano:	15 cm x 44 cm x 20 cm
Vano accessori:	10 cm x 44 cm x 36 cm
Misure:	Larghezza: 82 cm Profondità: 49 cm Altezza: 59 cm
Peso:	23,00 kg

Contenuto della confezione: