

OMNITRONIC Set CMX-2000 + 2x DD-5220L

Set with digital DJ mixer/controller and two turntables

Art.n.: 20000395

GTIN:



L'articolo non è più disponibile.

Features :

- 2-channel DJ mixer/MIDI controller bundled with Virtual DJ
- Optimized layout for Virtual DJ and Traktor PRO 2 - Virtual DJ 7 LE voucher included
- Traktor PRO 2 and Serato Scratch Live mappings available with full support for scratch and sample decks
- Flexibly combines stand-alone mixing of analog sources with MIDI control for DJ software
- Built-in DVS audio system for direct use of timecode systems with vinyl or CD in Virtual DJ and other open applications via USB
- 2 input channels with routing facility for analog inputs and MIDI decks as desired
- Full-fledged MIDI sections with 2 layers for 4-deck control
- Perfect MIDI control for file browsing, transportation, hot cues, samples, sample recorder, loops, effects, pitch und video transitions
- Advanced setup options for scratch DJs: crossfader and channel faders with adjustable curve and reverse selectors
- Built-in USB sound card 4 IN/4 OUT
- Supports Mac OSX, Windows XP, Vista, 7
- Professional-grade metal chassis with replaceable crossfader (45 mm)
- 2 line and 2 line/phono RCA inputs for connecting CD players, turntables and other external hardware
- 2 AUX inputs (3.5 mm/6.3 mm jack) connect MP3 players and tablets
- Mic input (XLR/6.3 mm jack) with tone control and talkover
- 2 master outputs (XLR/RCA) for PA applications
- Booth output (RCA), independently adjustable
- 3.5 mm/6.3 mm jack dual headphones output with cue mix control
- Bright color-coded LED buttons provide optimal visual feedback while triggering loops, samples, effects and cue points
- User-definable LED modes for Serato Scratch Live

Logistica

- Dual-function audio/video crossfader for video performances within Virtual DJ
- 3-band EQ (high, mid, low) and HP/LP filter per channel
- Mixer section switchable between analog mode and MIDI mode
- File selector encoder and 2 load buttons for mouseless music library control
- 8 Hot Cue buttons per channel
- Auto Loop function with Beat Jump (Loop Cut), manual Loop In/Out buttons
- FX/sampler units with 4 parameter controls and 4 buttons per channel
- Various controls for GUI, mixer and video
- Shift button for various dual-button operations
- Separate VU meters for master and PFL signal
- Crossfader with faderstart function for compatible CD players
- Compatible to any MIDI-controlled DJ software including Serato Scratch Live, Traktor, Ableton Live
- All MIDI control elements can be edited and freely assigned
- ASIO drivers with minimum latency and high-quality audio characteristics available for download (PC)
- The device can be connected via USB to the PC in connection with Virtual DJ
midi capable
- <p>OMNITRONIC DD-5220L Turntable bk
- Direct drive DJ turntable "Ultra Torque" with switchable phono/line output**
- Direct drive high-torque motor Quartz-controlled for highest speed precision
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control $\pm 10\%$, $\pm 20\%$, $\pm 50\%$
- Selectable quartz-controlled pitch lock
- Quick start
- Adjustable start/stop time
- 2 large start/pause buttons
- Reverse run
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing and adjustable feet
- Switchable phono/line output
- Extremely resonance-free due to optimally combined components
- Platter and motor are directly connected for highest stability
- Recessed connections for easy case mounting
- Delivery includes headshell, slipmat and RCA cable
- Dust cover and pick-up system optionally available
- Impostazione del passo: $\pm 10\%$, $\pm 20\%$, $\pm 50\%$

Dati tecnici :

Peso:	26,50 kg
-------	----------

OMNITRONIC CMX-2000 2+1-channel MIDI controller

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	14 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Collegamento USB:	USB 2.0, type B
PC connect:	Virtual DJ via USB Midi capable
Misure:	Larghezza: 36 cm Profondità: 26,5 cm Altezza: 10,5 cm

Peso:	3,90 kg
Inputs:	
Line:	2 x stereo RCA
Line/phono:	2 x stereo RCA, switchable
DJ microphone:	combination XLR/6.3 mm jack, bal.
Aux:	3.5 mm jack and stereo RCA
Outputs:	
Master:	XLR L/R and stereo RCA
Booth:	stereo RCA
Headphones output:	3.5 mm and 6.3 mm jack
Converter:	16 bits
Sample rate:	48 kHz
Faderstart:	2 x 3.5 mm jack

OMNITRONIC DD-5220L Turntable bk

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	15,00 W
Classe di protezione:	CL I
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina europea
Intervallo di frequenza:	20 - 20000 Hz
Tipo di trazione:	Quarz-controlled direct drive Motore brushless a corrente continua
Azionamento:	Coppia di avviamento: 4,5 kg/cm Tempo di avviamento: 0.2 - 6 sec, adjustable Tempo di decelerazione: 0.2 - 6 sec, adjustable Transizione di velocità: <1s 1kHz 5cm/sec
Flutter:	<0,1 % WRMS
Rombo:	60 dB DIN B
Regime:	33 Giri/min; 45 Giri/min; 78 Giri/min avanti/indietro
Braccio di riproduzione:	A forma di S con sospensione cardanica Length: 230 Tonearm heigh: 8 - 10.5 mm adjustable Overhang: 15 mm Stylus pressure: 0-4 g, regolabile
Livello di uscita:	Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec
Collegamenti:	Uscita: line/phono via 1 x RCA stereo
Impostazione del passo:	±10%, ±20%, ±50%
Misure:	Larghezza: 45 cm Profondità: 35,3 cm Altezza: 15,6 cm
Peso:	11,30 kg
Materiale:	Metallo
Misure:	Diametro: Ø 33,2 cm

Peso:

1,425 kg

Contenuto della confezione:

1 x Dispositivo
1 x Cavo di rete/Cavo di alimentazione
1 x Piatti per fonografi
1 x Tappetino in feltro
1 x set Shell
1 x Masse di equilibratura
1 x connettore
1 x adattatore
1 x cavo RCA
1 x Manuale d'uso