

EUROLITE ML-56 CDM Multi Lens Spot bk

Spot for CDM-T 150 discharge lamp with 4 lenses/beam angles

Art.n.: 41600125

GTIN: 4026397408423



Features :

- Spot with 4 exchangeable lenses (VNSP, NSP, MFL and WFL)
- Light output of a conventional PAR 56 spot with less power consumption
- High-quality die-cast housing for highest stability
- High-quality aluminum reflector
- Controllabile via plug and play
- Per campi di applicazione come, ad esempio,: Allestimenti per fiere e negozi

Logistica

EAN / GTIN: 4026397408423

Peso : 7,35 kg

Lunghezza : 0.28 m

Larghezza : 0.28 m

Altezza : 0.53 m

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	155 W
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Tipo di lampada:	Lampada a scarica
Generazione del colore:	Tramite cornice con filtro a colori
Attivazione:	Plug and play
Angolazione del fascio di luce (1/2 picco):	NSP 20° x 36° MFL 21° x 36° WFL 30° x 53° VNSP 15° x 36°
Colore della custodia:	Nero

Misure:	Larghezza: 28 cm
	Profondità: 22 cm
	Altezza: 40 cm
Peso:	6,75 kg

Contenuto della confezione: