

EUROLITE LED ML-56 COB 3200K 80W Floor sil

ML spot with 80 W COB LED in warm white

Art.n.: 41604047

GTIN: 4026397531688



Features :

- Functions: dimmer, strobe effect, Master/Slave operation, different dimmer curves/dimmer speed (step response)
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 1 or 3 DMX channels selectable
- Strobe effect with adjustable speed
- Beam angle approximately 35°
- Comfortable addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Ideal for theatres, large stages as pre-stage spot and mobile use
- With color filter frame, optional barndoors available
- Ready for connection with power cord and safety plug
- Switch-mode power supply for operation between 100 and 240 Volts
- Available in silver or in black
- 1 LED 80 W COB (chip-on-board) bianco caldo (WW)
- Effetto stroboscopico
- Può funzionare in modalità 1; 3 CH DMX
- Controllabile via DMX
- Senza sfarfallio
- With a beam angle of 35°

Logistica

EAN / GTIN: 4026397531688

Peso : 4,05 kg

Lunghezza : 0.29 m

Larghezza : 0.29 m

Altezza : 0.39 m

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	80 W
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Tipo di lampada:	Lampada a LED
Tipo di LED:	1 x 80 W COB (chip-on-board) bianco caldo (WW)
Frequenza di lampeggiamento:	0 - 17 Hz
Canali DMX:	1; 3
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Attivazione:	DMX
Fixtures disponibili per:	LED PC-Control 512; Light´J
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	35°
Angolazione del fascio di luce (1/2 picco):	35°
Angolazione del fascio di luce (1/10 di picco):	79°
Temperatura colore:	3200K
Colore della custodia:	Argento
Misure:	Larghezza: 29 cm Profondità: 25,5 cm Altezza: 32 cm
Peso:	3,55 kg

Contenuto della confezione:

1 x telaio filtro