

EUROLITE LED PMC-8x30W COB RGB MFL

COB Performance Cluster with 25° beam angle

Art.n.: 41606450

GTIN: 4026397507805



L'articolo non è più disponibile.

Features :

- Operable in stand-alone mode via control panel with LCD screen or in DMX mode
- Equipped with 8 x 30 W COB LEDs in the colors red, green and blue
- Each LED can be controlled individually
- Functions: Static colors, RGB color mixture, automatic color change, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Dimmer speed (step response) controllable
- Adjustable white balance
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Ideal as floor spot via base for standing installation
- Locking possibility at the mounting bracket
- With barn doors
- Neutrik powerCON terminals for power linking up to 8 units
- 8 LED 30 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea)
- Effetto stroboscopico
- Può funzionare in modalità 3; 4; 5; 6; 12; 24; 28; 33 CH DMX
- Controllabile via DMX; controllo della musica via microfono; RDM
- With a beam angle of 25°

Logistica

EAN / GTIN: 4026397507805

Peso : 7,60 kg

Lunghezza : 0.41 m

Larghezza : 0.24 m

Altezza : 0.29 m

Dati tecnici :

Alimentazione elettrica: 100-240 V AC, 50/60 Hz

Potenza totale installata: 220,00 W

Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x PowerCON (grigio), versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	8 x 30 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea)
Frequenza di lampeggiamento:	0 - 18 Hz
Canali DMX:	3; 4; 5; 6; 12; 24; 28; 33
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso 1 x Versione da incasso XLR (M) a 5 poli
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso 1 x Versione da incasso XLR (F) a 5 poli
Attivazione:	DMX; controllo della musica via microfono; RDM
Fixtures disponibili per:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Angolazione del fascio di luce:	25°
Angolazione del fascio di luce (1/2 picco):	25°
Angolazione del fascio di luce (1/10 di picco):	46°
Colore della custodia:	Nero
Misure:	Larghezza: 35,8 cm Profondità: 17,4 cm Altezza: 22,3 cm
Peso:	7,05 kg

Contenuto della confezione: