

EUROLITE LED ML-56 COB RGB 100W Floor sil

ML spot with 100 W COB LED and RGB color mixing

Art.n.: 41607321

GTIN: 4026397588279



Descrizione :

ML spot with 100 W COB LED and RGB color mixing

The Eurolite LED ML-56 spotlight is equipped with a 100 Watts Chip-on-Board (COB) LED in RGB colors, which ensure homogeneous color mixing. It is suitable for use in theatres, on large stages as a front spotlight and for mobile use. Because of the additional stand bracket, the ML-56 can also be used as a floor spot.

The effect spotlight comes with a variety of functions: Automatic color change, internal and user-defined programs, dimmer and strobe effect with variably adjustable speed. The flicker-free projection even makes it possible to use the spotlight for video recording.

You can control the Eurolite LED ML-56 COB via DMX with master/slave function or in standalone mode. In addition, the built-in microphone allows you to operate the spotlight via music control.

Comfortable addressing and setting is possible via the Control Board with four operating keys and LED display.

Logistica

EAN / GTIN: 4026397588279

Peso : 4,00 kg

Lunghezza : 0.29 m

Larghezza : 0.29 m

Altezza : 0.39 m

Features :

- Equipped with one COB 100 W LED in RGB colors
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Adjustable white balance
- Dimmer speed (step response) adjustable
- Stand-alone, master/slave and DMX mode
- Color presets can be called up via DMX controller
- Strobe effect with adjustable speed
- 40° beam angle

- Control panel with LED display for easy configuration
- Additional bracket for floor use
- 2 swivel mounting brackets
- With color filter frame
- Optional barndoors available
- Ideal for theatres, large stages as pre-stage spot and mobile use
- Various versions available
- 1 LED 100 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea)
- Effetto stroboscopico
- Può funzionare in modalità 3; 5; 6; 9 CH DMX
- Il dispositivo è raffreddato tramite Ventola
- Controllabile via DMX; controllo della musica via microfono
- Senza sfarfallio
- With a beam angle of 40°

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	90 W
Classe di protezione:	CL I
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Lunghezza cavo:	Circa 1,2 m
Tipo di lampada:	Lampada a LED
Tipo di LED:	1 x 100 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea)
Frequenza di lampeggiamento:	0 - 17 Hz
Canali DMX:	3; 3 (HSV hue/saturation/value); 5; 6; 9
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Raffreddamento:	Ventola
Attivazione:	DMX; controllo della musica via microfono
Fixtures disponibili per:	EASY SHOW 1; Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	40°
Angolazione del fascio di luce (1/2 picco):	40°
Angolazione del fascio di luce (1/10 di picco):	82°
Colore della custodia:	Argento
Misure:	Larghezza: 31 cm Profondità: 26 cm Altezza: 30 cm
Peso:	3,41 kg
Classificazione del rumore:	Classe 3 (rumori chiaramente percettibili)

Contenuto della confezione:

1 x telaio filtro