

EUROLITE PAR-64 Spot Long with Cable bk

Long PAR-64 housing (with open cable ends)

Art.n.: 42100960

GTIN: 4026397663297



L'articolo non è più disponibile.

Features :

- Durable aluminum cabinet
- Strong aluminum mounting bracket
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Blackened tube for precise light output
- Strong brass clamps with extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Color filter frame included in delivery
- Strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends
- Per PAR 64

Logistica

EAN / GTIN: 4026397663297

Peso : 2,22 kg

Lunghezza : 0.00 m

Larghezza : 0.00 m

Altezza : 0.00 m

Dati tecnici :

Alimentazione elettrica:

230 V AC, 50 Hz

Potenza totale installata:	Massimo 1000 W
Classe di protezione:	CL I
Allacciamento elettrico:	Pavimento cavo di collegamento con estremità aperte
Lunghezza cavo:	Circa 0,7 m
Attacco/Portalampada:	GX16d
Tipo di lampada:	Liberamente configurabile
Generazione del colore:	Via color filter frame (optional)
Colore della custodia:	Nero
Assorbimento nel proiettore:	25,7 cm x 25,7 cm
Misure:	Lunghezza: 42,5 cm Larghezza: 26,5 cm Altezza: 27 cm
Peso:	1,97 kg
Misure:	Lunghezza: 25,5 cm Larghezza: 25,5 cm Diametro: Ø 20,2 cm

Contenuto della confezione:

1 x Proiettori
 1 x telaio filtro
 1 x anello di bloccaggio della lampada
 1 x Manuale d'uso