

EUROLITE LED KLS-2500 Compact-Light-Set

Bar with 4 spots with 7 x 10 W 5in1 LED each, with 5-pin QuickDMX connector

Art.n.: 42109892

GTIN: 4026397517163



Features :

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- 7 PCL LEDs (RGBAW) per spot
- Comes pre-assembled with practical transport bag
- Movable and tiltable spotlights
- Sound-control via built-in microphone with sensitivity control
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom fed socket for QuickDMX receiver (see accessories)
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional foot pedal FP-1
- DMX512 control via regular DMX controller (occupies 28 channels)
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with OLED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and PowerCon input
- 4 IEC outputs for power supply of further devices
- 7 LED 10 W high power 5in1 RGBWA (miscela di colori omogenea)
 Spot controllabili singolarmente
- Può funzionare in modalità 2; 3; 4; 7; 20; 23; 28 CH DMX

Logistica

EAN / GTIN: 4026397517163

Peso : 16,70 kg

Lunghezza : 1.26 m

Larghezza : 0.13 m

Altezza : 0.40 m

Merci voluminose

- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; DMX; telecomando a pedale cablato (opzionale)
- With a beam angle of 17°

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	190,00 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x PowerCON (grigio), versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	7 x 10 W high power 5in1 RGBWA (miscela di colori omogenea)
Canali DMX:	2; 3; 4; 7; 20; 23; 28
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; DMX; telecomando a pedale cablato (opzionale)
Fixtures disponibili per:	Light' J; LED PC-Control 512; EASY SHOW 1; Light Captain
Angolazione del fascio di luce:	17°
Angolazione del fascio di luce (1/2 picco):	17°
Angolazione del fascio di luce (1/10 di picco):	30°
Colore della custodia:	Nero
Misure:	Larghezza: 120 cm Profondità: 6 cm Altezza: 32 cm
Peso:	15,70 kg
DMX channels:	2/3/4/7/20/23/28
DMX connection:	3-pin XLR
QuickDMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED type:	10 W RGBAW (5in1)
Number of LEDs:	28
Beam angle:	28°
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1160 x 60 x 320 mm

Contenuto della confezione:

1 x Proiettori