# ANTARI DarkFX Strip 510

PRO UV LED bar with 6 x 1.9 W UV LED, deep UV wavelength (365 nm)

**Art.n.: 51100822**

GTIN: 4719850658045





## L'articolo non è più disponibile.

### Descrizione :

The Antari DarkFX Strip 510 is an efficient high-output and low-power consumption UV LED bar that delivers a peak wavelength of 365nm and radiant flux output of 4500 mW at full intensity with minimum visible light. This ensures all UV-reactive materials reflect perfectly with stunningly bright and vivid colors.
Equipped with 6 x 1.9 W high-power UV LEDs, it features a 25° narrow beam angle, flicker-free operation, and special optics to prevent wear degradation from high UV exposure. This IP20-rated LED bar comes with an aluminium housing with an adjustable bracket for versatile mounting options.
The Antari DarkFX Drive 4 or Drive 4 MKII fixture driver (sold separately) is required for power and DMX control.

### Logistica

EAN / GTIN: 4719850658045
Peso : 1,50 kg
Lunghezza : 0.63 m
Larghezza : 0.10 m
Altezza : 0.10 m

### Features :

- Luce visibile minima
- Alte prestazioni a piena intensità
- Special optics will not degrade due to high UV exposure
- Power supply and DMX control via optional Antari DarkFX Drive 4 fixture driver
- 6 LED 1,9 W high power ultravioletto (UV)
- Effetto UV
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Senza sfarfallio
- With a beam angle of 25°
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

## Dati tecnici :

| | |
|---|---|
| Alimentazione elettrica: | 20-24V DC |
| Potenza totale installata: | 12 W |
| Allacciamento elettrico: | Pavimento cavo di collegamento con estremità aperte |
| Tipo di lampada: | Lampada a LED |
| Tipo di LED: | 6 x 1,9 W high power ultravioletto (UV) |
| Raffreddamento: | Raffreddamento a convezione passiva |
| Proiezione: | Senza sfarfallio |
| Angolazione del fascio di luce: | 25° |
| Angolazione del fascio di luce (1/2 picco): | 25° |
| Lunghezza d'onda: | 365 nm |
| Colore della custodia: | Nero |
| Materiale: | Metallo |
| Misure: | Larghezza: 59,3 cm<br>Profondità: 7,4 cm<br>Altezza: 7,2 cm |
| Peso: | 1,25 kg |

## Contenuto della confezione:

1 x Dispositivo
1 x Manuale d'uso
2 x Supporto

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.