



Features :

- For highlighting individual object parts
- Very high brightness
- Easy processing
- Simple means - big effect
- Paintings and bar decoration
- Discotheque truss systems decoration
- Applicable on all surfaces, e.g. wood, metal, plastic
- Outstanding hide and coverage
- Very high luminosity as soon as the uv light falls on the lacquered object
- The optional EUROLITE primer increases luminosity
- The optional EUROLITE protection varnish preserves the color
- Easy application by brush, roller or sprayer
- High yield

Logistica

EAN / GTIN: 4026397023015
Peso : 0,95 kg
Lunghezza : 0.10 m
Larghezza : 0.10 m
Altezza : 0.12 m

Dati tecnici :

Practical coverage:	approx. 90-100 ml per m ²
Dry time to touch:	aprx. 4-5 hours
Dry time to recoat:	approx. 24 hours
Applicable thinner:	Universal thinner
Contents:	Xylol, toluol, ethylbenzol, oropylbenzol, 1.3.5 trimethylbenzol, inflammable crude oil distillates

Boiling point:	135-160° C
Flash point:	26° C
Ignition temperature:	450° C
Density:	1-1.3 g / cm ³ (dependent on color)
Solvent percentage:	23 + 3%

Contenuto della confezione:
