FUTURELIGHT CP-256 MST controller 16bit

DMX controller with Pendrive

Art.n.: 51834290

GTIN: 4026397280265











Descrizione :

Keep up-to-date!
The world doesn't stand still, it always keeps on turning. That is also true for technical developments, that are fast and ever move on. Therefore, you have to adapt yourself and if necessary, your environment to these processes. And if you examine our new CP-256 MST controller, you will realize, that we have adapted to the scenery. Because besides the accustomed benefits such as the 16 bit resolution or the comprehensive projector library, this controller distinguishes itself through its USB-slot. This slot enables you to to use a USB-port as external memory. A fact, that will not only please the controlled intelligent light, right?

Features :

- 512 control channel for 16 projectors with up to 32 channels
- 16 bit resolution for fine Pan/Tilt movements
- Comprehensive projector library
- USB Pendrive for memory back up, loading fixture profiles and software updates (up to 2 GB)
- 64 programs
- 64 records
- 64 Preset Scenes
- 10 selectable languages
- Mirror-movement direction can be inverted
- Copy-function for the scenes, programs and records
- 64 Sequences
- Blackout-function
- Sound control via built-in microphone or Audio-socket
- Security code operation
- Operating hour meter

Logistica

EAN / GTIN: 4026397280265
Peso : 4,15 kg
Lunghezza : 0.65 m
Larghezza : 0.25 m
Altezza : 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

- Software-update possible via optional accessory
- Rack installation with 4 units

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	6,00 W
Misure:	Larghezza: 48,3 cm Profondità: 13,4 cm Altezza: 8,9 cm
	via 12-15 V DC, 500 mA power unit included in the delivery
Number of control channels:	512
Sound-control:	either via 6.3 mm Jack or built-in microphone
Sound-input:	6.3 mm stereo Jack
Audio-sensitivity:	0.3-1 V
DMX512 output:	3-pin XLR connector
Free chasers:	64
Dimensions (L x W x H):	483 x 176 x 83 mm
	Rack installation with 4 u
Minimum mounting depth:	90 mm
Weight:	3.6 kg

Contenuto della confezione:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.