

FUTURELIGHT PRO Slim PAR-12 MK2 TCL

Flat PRO LED spotlight with 12 x 9 W 3in1 LED (RGB) without fan

Art.n.: 51842562

GTIN: 4026397614015



Descrizione :

Flat, professional LED spot without fan

The FUTURELIGHT PRO Slim PAR-12 MK2 TCL is equipped with 12 powerful 3in1 tricolor LEDs in red, green and blue. The slim spot is suitable for use on larger stages and in discotheques. Thanks to the pure convection cooling, you can also use it in theatres or at galas, because it is noiseless in operation. Due to the compact and flat housing, you only need minimal space during installation.

The LEDs with RGB color mixing produce rich and homogeneous colors. The flicker-free Slim Spot is dimmable and has strobe settings with variable speed.

Several devices can be synchronised in master/slave mode. Powercon mains connections are located at the rear of the unit, allowing up to eight units to be operated in series. The LED spot can be controlled via DMX or in stand-alone mode.

Features :

- Equipped with 12 x 3in1 tricolor LEDs in the colors red, green and blue
- Flat housing form requires minimal space when rigging
- Extremely compact housing in a beautiful design
- Second mounting bracket for safe standing installation
- Locking possibility at the brackets with large metal butterfly screws
- Functions: static colors, RGB color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation
- Microphone-sensitivity adjustable via Control Board
- Addressing and setting via Control Board with four operating buttons and LED display
- Operable in stand-alone mode or via DMX

Logistica

EAN / GTIN: 4026397614015

Peso : 5,50 kg

Lunghezza : 0.25 m

Larghezza : 0.25 m

Altezza : 0.30 m

- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 12 LED 9 W high power 3in1 RGB (miscela di colori omogenea)
- Effetto stroboscopico
- Può funzionare in modalità 3; 5; 7 CH DMX
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; DMX; controllo della musica via microfono
- Senza sfarfallio
- With a beam angle of 9°
- Funzionamento silenzioso

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	85 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite P-Con (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x P-Con (grigio), versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	12 x 9 W high power 3in1 RGB (miscela di colori omogenea)
Canali DMX:	3; 5; 7
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; DMX; controllo della musica via microfono
Fixtures disponibili per:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	9°
Angolazione del fascio di luce (1/2 picco):	9°
Angolazione del fascio di luce (1/10 di picco):	20°
Colore della custodia:	Nero
Misure:	Larghezza: 28,7 cm Profondità: 12,6 cm Altezza: 30 cm
Peso:	5,00 kg
Classificazione del rumore:	Classe 0 (nessun rumore)

Contenuto della confezione:

- 1 x Proiettori
- 1 x Manuale d'uso
- 1 x Cavo di rete/Cavo di alimentazione