

EUROLITE USB Interface 2x512 DMX/Artnet incl. 64x DMX512 Control Software

Interfaccia USB per 2 universi DMX e 3 software di controllo dell'illuminazione

Art. n.: 51860171

GTIN: 4026397674996



L'articolo non è più disponibile.

Descrizione :

Matrix configurations

Create all kinds of matrix configurations. Pixel Control includes a complete and powerful patch tool to setup DVI, DMX ArtNet, 3D matrix and LED strips. It can also create a matrix combined with different types of fixtures and with additional type of DMX channels (not RGB).

Graphic effects & transitions on 64 universes

Shapes your selections to play the desired effects and quickly select your transitions to animate your show. Up to 64 universes management for 32,768 channels, 10,922 RGB pixels or 1280x1024 DVI resolution.

Synchronized show to perfection

Create a synchronized show with your own audio and video files and add marker points in the timeline to specify essentials steps of your show.

Great visual effect quality

Integrate a large number of amazing graphic effects and visuals from a library with audio, videos, animations, shapes, GIF and pictures to make every project unique and beautiful. Just overlay several effects on different layer to get unlimited combination.

Easy triggers and patch setup

Play your show via simple trigger buttons. Prepare and program your show in advance and run it through Ethernet, Midi, keyboard, USB device or DMX triggers. All types of paths are possible, like 2D and 3D, multiple matrices, custom shapes, LED strips and high DVI resolutions.

Logistica

EAN / GTIN: 4026397674996

Peso : 0,27 kg

Lunghezza : 0.20 m

Larghezza : 0.14 m

Altezza : 0.06 m

Features :

- Controllo del PC a LED (illuminazione dell'architettura)
- Controllo DMX (controllo della luce dello spettacolo)
- Controllo dei pixel (mappatura dei pixel e video mixing)
- 64 universi Art Net con 512 canali ciascuno tramite Ethernet
- 32.768 canali singoli o 10.922 pixel RGB
- Uscita in alta risoluzione DVI (1024 x 768 pixel)
- Supporta il controllo del touchscreen
- Può inviare fino a 1024 canali DMX
- Controllabile via DMX
- The device can be connected via USB to the PC
- Per campi di applicazione come, ad esempio,: Club/scuole di danza; Allestimenti per fiere e negozi; installazione; Ristoranti, bar e hotel

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite Micro USB (F) versione da incasso cavo di alimentazione per collegamento alla rete USB A (in dotazione)
Canali DMX:	Uscita 1024
Uscita DMX:	2 x XLR (F) a 3 poli versione da incasso
Attivazione:	DMX
Collegamento USB:	USB 2.0, type mini USB (F) versione da incasso
Colore:	Nero
PC connect:	Via USB
Misure:	Larghezza: 7 cm Profondità: 9 cm Altezza: 4,5 cm
Peso:	0,18 kg

Contenuto della confezione:

1 x Dispositivo
1 x Cavo USB