EUROLITE LED FLD-432 RGB 10mm Flood

High performance LED RGB floodlight

Art.n.: 51913851

GTIN: 4026397297317











Descrizione :

Bright as lightning!
All wine are not created equal, just as all lights are not created equal as well. The former is distinguished between vintage, finish or bouquet. Concerning light, characteristics like color, warmth and brightness are to the fore. Seeing the performance of our EUROLITE Flood Light and its 432 LEDs, you will understand, that lights can be differenced from one another quite clearly. Our flood light for example, can surpass its competitors in the field of brightness and enlightens a DJ's backplane on stage with great colors. This device provides the facility ether to enlighten all of its eight segments separately and in different colors or to let them shine in the same color at the same time. Furthermore, this product can easily replace an conventional spot like a PAR 56 and by doing so, saves energy due to its low power consumption. Ain't that bad.

Features :

- Equipped with 432 x 10 mm LED (red: 18 x 8, green: 18 x 8, blue: 18 x 8)
- Manual, sound or DMX-controlled operation
- Functions: static colors; automatic color change, 14 built-in programs and strobe effect with variable speed; Master/Slave
- On-bord control bord with 2 x 8 character LC-display
- DMX512 control possible via any commercial DMX controller
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety power plug
- Può funzionare in modalità 26 CH DMX
- Controllabile via controllo della musica via microfono

Logistica

EAN / GTIN: 4026397297317
Peso : 5,30 kg
Lunghezza : 0.62 m
Larghezza : 0.26 m
Altezza : 0.19 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	60 W
Canali DMX:	26
Attivazione:	Controllo della musica via microfono
Angolazione del fascio di luce (1/2 picco):	30°
Misure:	Larghezza: 54 cm Profondità: 19 cm Altezza: 13,4 cm
Peso:	4,75 kg
Light ouput intensity:	R 30000 mcd
	G 30000 mcd
	B 20000 mcd
Beam angle:	20°
DMX channels:	Max. 26
LED number:	432 (10 mm)
Dimensions (L x W x H):	540 x 190 x 134 mm

Contenuto della confezione:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.