

EUROLITE LED PAR-64 QCL 12x8W floor sil

PAR spot with 12 x 8 W 4in1 LED and RGBW color mixing

Art.n.: 51914031

GTIN: 4026397613841



Descrizione :

PAR spotlight with RGBW color mixing incl. remote control

The Eurolite LED PAR-64 is equipped with 12 powerful RGBW-LEDs (4in1) of 8 Watt each. You can use it on stage, in the club lighting area or as a floor spot, thanks to its additional bracket for placement.

The color temperature of the white tone is adjustable in six steps, the RGBW color mixing is stepless. 24 colors can be selected directly. The spotlight has a dimmer and strobe effect.

The effect spot can be controlled via DMX, standalone or via music control via the built-in microphone with adjustable microphone sensitivity. In auto and music mode you can play the integrated show programs.

Addressing and settings are possible via a control unit with four-digit LED display. Up to eight devices can be easily interconnected using the existing IEC mains connections.

The Eurolite LED PAR-64 can be easily remote controlled with the supplied infrared remote control.

Features :

- 12 high-power 8 W RGBW LEDs (4in1)
- Built-in auto and music show programs
- Color temperature adjustable in 6 steps (2700-8000 K)
- Direct color selection for 24 preset colors
- Stepless RGBW color blend, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Swivel mounting bracket

Logistica

EAN / GTIN: 4026397613841

Peso : 3,00 kg

Lunghezza : 0.26 m

Larghezza : 0.26 m

Altezza : 0.34 m

- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- 12 LED 8 W high power 4in1 RGBW (miscela di colori omogenea)
- Effetto stroboscopico
- Può funzionare in modalità 2; 3; 4; 5; 6; 9 CH DMX
- Controllabile via stand-alone; DMX; Telecomando IR; controllo della musica via microfono; funzione master/slave
- Senza sfarfallio
- With a beam angle of 14°

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	70 W
Classe di protezione:	CL I
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x dispositivi a freddo (F) versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	12 x 8 W high power 4in1 RGBW (miscela di colori omogenea)
Canali DMX:	2; 3; 4; 5; 6; 9
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Attivazione:	Stand-alone; DMX; Telecomando IR; controllo della musica via microfono; funzione master/slave
Fixtures disponibili per:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	14°
Angolazione del fascio di luce (1/2 picco):	14°
Angolazione del fascio di luce (1/10 di picco):	29°
Colore della custodia:	Argento
Misure:	Larghezza: 29,6 cm Profondità: 27,3 cm Altezza: 34 cm
Peso:	2,60 kg
Pila:	1 x pila a bottone 3,0 V CR2025 litio-manganese montato

Contenuto della confezione:

1 x telecomando