

EUROLITE LED IP CCR-1200 QCL Wall Light incl. Flight Case

PRO outdoor spotlight (IP65) in case with 120 x 8 W 4in1 LED (RGBW)

Art.n.: 51914134

GTIN: 4026397573152



Features :

- DMX-controlled operation or stand-alone operation with Master/Slave function
- DMX control via any standard DMX controller
- 4, 7, or 11 DMX channels selectable
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- For architectural lighting
- Suitable for external use (IP65)
- For permanent installation
- Equipped with 120 x 4in1 QCL LED in the colors red, green, blue and white
- Stepless RGBW color blend
- Color macros
- Dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Internal programs
- Programmable color change speed
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- Ready for connection via power cord with 3-pin 16A CEE plug
- Flightcase included in delivery
- 120 LED 8 W high power 4in1 RGBW (miscela di colori omogenea)
- Può funzionare in modalità 4; 7; 11 CH DMX
- Il dispositivo è raffreddato tramite Ventola
- Controllabile via stand-alone; DMX; W-DMX by wireless solution
- Senza sfarfallio
- With a beam angle of 15°

Logistica

EAN / GTIN: 4026397573152

Peso : 55,00 kg

Lunghezza : 0.72 m

Larghezza : 0.50 m

Altezza : 0.80 m

Merci voluminose

- Adatto per uso esterno IP65

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	460 W
Grado di protezione:	IP65
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Tipo di lampada:	Lampada a LED
Tipo di LED:	120 x 8 W high power 4in1 RGBW (miscela di colori omogenea)
Frequenza di lampeggiamento:	0 - 18 Hz
Canali DMX:	4; 7; 11
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Raffreddamento:	Ventola
Attivazione:	Stand-alone; DMX; W-DMX by wireless solution
Fixtures disponibili per:	Light' J; LED PC-Control 512
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	15°
Angolazione del fascio di luce (1/2 picco):	15°
Angolazione del fascio di luce (1/10 di picco):	48°
Colore della custodia:	Nero
Misure:	Larghezza: 65 cm Profondità: 58 cm Altezza: 67 cm
Peso:	54,90 kg

Contenuto della confezione: