

EUROLITE LED IP PAD 9x8W QCL

Weather-proof DMX spot (IP65) with 9 x 8 W 4in1 LED (RGBW)

Art.n.: 51914158

GTIN: 4026397483024



Features :

- 4, 6 or 7 DMX channels selectable for numerous applications
- Equipped with 9 x 8 W 4in1 LED in the colors red, green, blue and white
- For architectural lighting
- Suitable for external use (IP65)
- Compact, matt grey housing
- Functions: Static colors, RGBW color mixture, built-in programs, dimmer, strobe effect, Master/Slave operation
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Infrared remote control in credit card format included in delivery
- Switch-mode power supply, automatic power supply adaption between 100 and 240 volts
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- 9 LED 8 W high power 4in1 RGBW (miscela di colori omogenea)
- Può funzionare in modalità 4; 6; 7 CH DMX
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; DMX; Telecomando IR
- With a beam angle of 15°
- Adatto per uso esterno IP65

Logistica

EAN / GTIN: 4026397483024

Peso : 4,75 kg

Lunghezza : 0.30 m

Larghezza : 0.20 m

Altezza : 0.31 m

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	65 W
Grado di protezione:	IP65
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore a vite a 3 poli (M) IP cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x connettore a vite a 3 poli (F) IP
Tipo di lampada:	Lampada a LED
Tipo di LED:	9 x 8 W high power 4in1 RGBW (miscela di colori omogenea)
Canali DMX:	4; 6; 7
Ingresso DMX:	1 x connettore a vite a 3 poli (M) IP
Uscita DMX:	1 x connettore a vite a 3 poli (F) IP
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; DMX; Telecomando IR
Fixtures disponibili per:	Light´J; LED PC-Control 512
Angolazione del fascio di luce:	15°
Angolazione del fascio di luce (1/2 picco):	15°
Colore della custodia:	Grigio
Misure:	Larghezza: 20,5 cm Profondità: 12 cm Altezza: 22,3 cm
Peso:	4,25 kg
Pila:	1 x pila a bottone 3,0 V CR2025 litio-manganese montato

Contenuto della confezione:

1 x telecomando