

## EUROLITE LED IP FL-80 COB RGB 120° RC

Outdoor floodlight (IP65) with 80 W COB LED (RGB) and IR remote control

Art.n.: 51914612

GTIN: 4026397552959



### Features :

- Add highlights to your house and garden
- Ideal LED luminary for indoor or outdoor use
- Weather-proof housing (IP65)
- Mounting bracket for permanent installation included
- Extremely compact housing in an appealing design
- Equipped with 1 COB RGB LED
- Beam reflection angle of 120°
- Ready for connection via power cord with safety-plug
- Automatic color change or manual program or color selection
- Built-in programs for color change and color fade
- Adjustable program speed and brightness
- Direct color selection for 15 preset colors + white
- Memory function for control programs via the Flash, Strobe, Fade and Smooth buttons of the IR remote control
- 1 LED 80 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea)
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; Telecomando IR
- With a beam angle of 120°
- Adatto per uso esterno IP65
- Funzionamento silenzioso
- **telecomando**
- Portata fino a 7m

### Logistica

EAN / GTIN: 4026397552959

Peso : 5,80 kg

Lunghezza : 0.39 m

Larghezza : 0.31 m

Altezza : 0.15 m

**Dati tecnici :**

|                                             |                                                                    |
|---------------------------------------------|--------------------------------------------------------------------|
| Alimentazione elettrica:                    | 100-240 V AC, 50/60 Hz                                             |
| Potenza totale installata:                  | 80 W                                                               |
| Grado di protezione:                        | IP65                                                               |
| Classe di protezione:                       | CL I                                                               |
| Allacciamento elettrico:                    | Pavimento cavo di alimentazione con spina di protezione            |
| Lunghezza cavo:                             | Circa 1,6 m                                                        |
| Tipo di lampada:                            | Lampada a LED                                                      |
| Tipo di LED:                                | 1 x 80 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea) |
| Raffreddamento:                             | Raffreddamento a convezione passiva                                |
| Attivazione:                                | Stand-alone; Telecomando IR                                        |
| Angolazione del fascio di luce:             | 120°                                                               |
| Angolazione del fascio di luce (1/2 picco): | 120°                                                               |
| Colore della custodia:                      | Argento                                                            |
| Misure:                                     | Larghezza: 28,3 cm<br>Profondità: 11 cm<br>Altezza: 38,3 cm        |
| Peso:                                       | 5,40 kg                                                            |
| Classificazione del rumore:                 | Classe 0 (nessun rumore)                                           |
| Pila:                                       | 1 x pila a bottone 3,0 V CR2025 litio-manganese montato            |
| Massima:                                    | Fino a 7m                                                          |

**Contenuto della confezione:**

- 1 x Proiettori
- 1 x telecomando
- 1 x Manuale d'uso