EUROLITE LED IP FL-100 COB RGB 120° RC

Outdoor floodlight (IP65) with 100 W COB LED (RGB) and IR remote control

Art.n.: 51914614

GTIN: 4026397552973





L'articolo non è più disponibile.

Features :

- Add highlights to your house and garden
- Ideal LED luminary for indoor or outdoor use
- Weather-proof housing (IP65)
- Mounting bracket for permanent installation included
- Extremely compact housing in an appealing design
- Equipped with 1 COB RGB LED
- Beam reflection angle of 120°
- Ready for connection via power cord with safety-plug
- Automatic color change or manual program or color selection
- Built-in programs for color change and color fade
- Adjustable program speed and brightness
- Direct color selection for 15 preset colors + white
- Memory function for control programs via the Flash, Strobe, Fade and Smooth buttons of the IR remote control
- 1 LED 100 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea)
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; Telecomando IR
- With a beam angle of 120°
- Adatto per uso esterno IP65
- Funzionamento silenzioso

  telecomando
- Portata fino a 7m

Logistica

EAN / GTIN: 4026397552973

Peso : 5,48 kg

Lunghezza : 0.40 m

Larghezza : 0.31 m

Altezza : 0.15 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	100 W
Grado di protezione:	IP65
Classe di protezione:	CL I
Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Tipo di lampada:	Lampada a LED
Tipo di LED:	1 x 100 W COB (chip-on-board) 3in1 RGB (miscela di colori omogenea)
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; Telecomando IR
Angolazione del fascio di luce:	120°
Angolazione del fascio di luce (1/2 picco):	120°
Colore della custodia:	Argento
Colore:	Trasparente
Misure:	Larghezza: 28,3 cm Profondità: 9,8 cm Altezza: 38 cm
Peso:	5,08 kg
Classificazione del rumore:	Classe 0 (nessun rumore)
Massima:	Fino a 7m

Contenuto della confezione:

1 x Proiettori
1 x telecomando
1 x Manuale d'uso

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.