

EUROLITE LED PUS-5 Hybrid flower effect

LED flower effect with strobe

Art.n.: 51918663

GTIN: 4026397459524



L'articolo non è più disponibile.

Features :

- Hybrid effect - LED flower and strobe in one device
- Absolute eyecatcher: groups of 5 mm RGBAW LEDs are arranged behind the 5 lenses; a double row of white SMD LEDs is arranged around the center lens
- Operable in stand-alone mode or with DMX512 interface
- DMX512 control possible via any commercial DMX controller (occupies max. 4 channels)
- 2 or 4 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Microphone sensitivity adjustable via rotary control
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Functions: Auto mode, sound control, internal programs, strobe settings via DMX, Master/Slave
- Equipped with 320 x 5mm RGBAW LEDs as well as 50 x SMD LEDs in white
- Convenient control also via Wi-Fi networks with your tablet or smartphone and the Eurolite Hybrid App plus the USB-DMX interface (item 51860120) and the light control software FreeStyler (freeware)
- Eurolite Hybrid App is available for free in the App Store
- Locking possibility at the mounting bracket
- Feed-through output allows to power up to 8 devices
- IEC power cord with safety-plug included in delivery
- Switch-mode power supply allows for automatic power supply adaption between 100 and 240 volts
- Controllabile via stand-alone; DMX

Logistica

EAN / GTIN: 4026397459524

Peso : 5,20 kg

Lunghezza : 0.43 m

Larghezza : 0.30 m

Altezza : 0.38 m

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	20,00 W
Tipo di lampada:	Lampada a LED
Attivazione:	Stand-alone; DMX
Fixtures disponibili per:	Light J
Colore della custodia:	Nero
Misure:	Larghezza: 24 cm Profondità: 32,5 cm Altezza: 34,5 cm
Peso:	4,30 kg
DMX channels:	2/4
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5mm-RGBAW / SMD-5050 white
LED number:	320 (R: 80, G: 80, B: 80, W: 40, A: 40) / 50
Beam angle:	40°
Dimensions DxBxH:	196 x 365 x 298 mm

Contenuto della confezione: