REUTLINGER Supporti per funi metalliche tipo 50SVIII-M12BG nero

Cable glider, up to 90 kg work load

Art.n.: 58010550

GTIN: 4026397595956





Descrizione :

Certified cable holder
Cable holders can be used for easily suspending static workloads on attachment ropes. No tools are required. The load can be hung at any position and height and easily be re-positioned.

The REUTLINGER cable holders are the only system certified by two independant certification bodies. This cable holder boasts of a TUV certificate and a German BGV C1 certificate and can be used in entertainment technology.

TÜV GS and BGV C1 - double-tested and double-certified
REUTLINGER® grippers type 50 SV III, type 66 SV III and type 80 SV III are not only certified as safe (GS) by the German TÜV, they have also been licensed for use within the scope of standard DGUV Regulation 17 (BGV C1).
The DGUV Test certificate authorises these grippers for use within the scope of the accident prevention regulations issued by the German employers' liability insurance associations in respect of staging and production facilities.
The test seal of the DGUV is conferred only after extensive examining of all load applications. Further testing simulated most anticipated mis-applications.
REUTLINGER® gripper ranges 50, 66 and 80 are the only load-bearing devices certified by the DGUV for use in mobile production facilities.

Features :

- Per il diametro della fune da 4,0 a 5,0 mm
- Meccanismo a 6 sfere
- Nota: i supporti per funi metalliche non devono essere utilizzati in modo dinamico e devono essere utilizzati almeno in coppia.
- Filettatura M12

Logistica

EAN / GTIN: 4026397595956
Peso : 0,13 kg
Lunghezza : 0.18 m
Larghezza : 0.12 m
Altezza : 0.03 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

- Made in Germany
- Certificato BG
- Certificato TÜV/GS
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

Per il diametro della fune:	4 mm - 5 mm
Carico di lavoro:	5 mm: 90 kg 4 mm: 60 kg
Colore:	Nero
Filettatura:	Filettatura M12 x 17 mm
Misure:	Lunghezza: 7 cm Diametro: Ø 2,50 cm
Peso:	0,12 kg

Contenuto della confezione:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.