SHZ Roundsling with Steel Inlay 3m/4000KG

Imbracatura rotonda con inserto in acciaio

Art.n.: 58010755

GTIN: 4026397466584









Features :

- Steelflex with window complies with BGV C1
- For attaching loads
- Made from polyester, complies with DIN EN 1492-2
- Single-coated, thermically fix
- Printed load capacity
- No danger of injury for the hands
- Smooth transport of goods
- Highly flexible
- UV resistant
- Complies with EN 1492-2
- La lunghezza utile è di 3 m

Logistica

EAN / GTIN: 4026397466584
Peso : 5,25 kg
Lunghezza : 0.39 m
Larghezza : 0.39 m
Altezza : 0.07 m

Dati tecnici :

Carico WLL (7 volte sup.) massimo:	4000 kg
Norma:	EN 1492-2,
Colore:	Nero
Intervallo di temperatura:	-40° C - +100° C
Lunghezza utile:	3 m
Peso:	5,25 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

Contenuto della confezione:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.