ALUTRUSS SINGLELOCK POWER PSP-1500 Tubo QUICK-LOCK

Art.n.: 60210197

GTIN: 4026397489699

Tubo a traversa semplice con connettori QUICK-LOCK





Prezzo di listino: 94.61 €

incl. 19% IVA

Descrizione :

SINGLELOCK PSP 1-point truss system
SINGLELOCK PSP is a 1-point truss system made of aluminum. The individual elements are connected via one cone, pivots and pins.

The advantage of the conical connection system is that the cone completely fits into the main chord so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The main chord is made of 50 mm aluminum tube with 3 mm wall thickness and offers a good relation between strength and weight.

SINGLELOCK PSP is a stable truss system for higher loads and extended durability. This system is mainly designed for intense use in stage installations, fair installations, event installations but also for permanent installations in discotheques and theatres.

With SINGLELOCK SP, decorative frames with advertising signs, transmission canvas etc. can be realized.

Features :

- Tubi in alluminio di alta qualità con un diametro di 50 mm
- Peso leggero
- Per la decorazione o la realizzazione di telai per pellicole di proiezione
- Montaggio facile
- Tubo della cinghia: 50 mm
- Adatto per Singlelock SP 1

Logistica

EAN / GTIN: 4026397489699
Peso : 2,25 kg
Lunghezza : 1.50 m
Larghezza : 0.06 m
Altezza : 0.06 m
Merci voluminose

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

- Disponibile su richiesta in qualsiasi colore RAL
- Disponibile in vari colori e dimensioni
- Made in Europe
- Per campi di applicazione come, ad esempio,: Allestimenti per fiere e negozi; palco; noleggiatore

Dati tecnici :

Struttura:	Montaggio facile
Tubo della cinghia:	50 mm x 3 mm
Processo di saldatura:	Impulso TIG
Materiale di saldatura:	AlMg 5
Materiale del tubo:	EN-AW 6082 T6 (AlSi1Mg)
Materiale:	Alluminio
Colore:	Color alluminio; disponibile su richiesta in qualsiasi colore RAL
Misure:	Lunghezza: 150 cm Diametro: Ø 5 cm
Peso:	2,24 kg

Contenuto della confezione:

1 x traversa
1 x set di connettori

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.