

ALUTRUSS DECOLOCK DQ4-1500 Traversa a 4 punti

Sistema di traverse universale a 4 punti in struttura leggera

Art.n.: 60301714

GTIN: 4026397388909



Descrizione :

DECOLOCK DQ4 4-point truss system

DECOLOCK DQ4 is a 4-point truss system made of aluminum. The individual elements are connected via four cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The four main chords are made of 35 mm aluminum tube with 2 mm wall thickness and offer sufficient strength at a low weight. The braces have a diameter of 10 mm with 2 mm wall thickness and provide the system with a decorative appearance.

With DECOLOCK, you can realize compact installations with low self weight, e. g. for shop displays, shop decorations, exhibitions, interior design, fair booths, discotheques and theatres.

DECOLOCK is primarily designed for decorative installations and can be used for permanent or temporary installations due to its highly aesthetic appearance. The advantages of this system are the compact construction with 220 mm outer dimensions, low weight, optimum strength along with easy and quick assembly.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

Logistica

EAN / GTIN: 4026397388909

Peso : 5,65 kg

Lunghezza : 1.50 m

Larghezza : 0.23 m

Altezza : 0.23 m

Merci voluminose

Features :

- La lega di alluminio per un look classico e high-tech
- Montaggio rapido, efficiente e affidabile tramite connettori a cono QUICK-LOCK
- Un'ampia selezione di lunghezze, elementi circolari e angolari offre la massima flessibilità
- Costruzioni speciali secondo le specifiche del cliente su richiesta
- Tubo della cinghia: 35 mm
- Disponibile su richiesta in qualsiasi colore RAL
- Disponibile in vari modelli
- Certificato TÜV Süd
- Per campi di applicazione come, ad esempio,: Teatro; Allestimenti per fiere e negozi; installazione; palco
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

Tubo della cinghia:	35 mm x 2 mm
Processo di saldatura:	Impulso TIG
Materiale di saldatura:	AlMg 5
Colore:	Color alluminio; disponibile su richiesta in qualsiasi colore RAL
Spessore x diametro del puntone:	10 x 2mm
Misure:	Lunghezza: 150 cm Larghezza: 22 cm Altezza: 22 cm
Peso:	5,05 kg

Contenuto della confezione:

1 x set di connettori